

Complete Insulated Program



Supporting Arc Flash Protection





Arc Flash Protection:

Wiha Insulated tools can be a vital component in your Arc Flash protection strategy. What is Arc Flash?

ARC FLASH

An Arc Flash is an electrical explosion due to a fault condition or short circuit when either a phase to ground or phase to phase conductor is connected. Arc flashes cause electrical equipment to explode, resulting in an arc-plasma fireball. Temperatures may exceed 35,000° F (the surface of the sun is 9000° F). These high temperatures cause rapid heating of surrounding air and extreme pressures, resulting in an arc blast. The arc blast will likely vaporize all solid copper conductors which will expand up to 67,000 times its original volume when it is vaporized. The result of this violent event is usually destruction of the equipment involved, fire, and severe injury or death to any nearby people.

WHY ARC FLASHES HAPPEN

There are a variety of reasons why an Arc Flash can occur, but most of them are preventable. Most arc flashes occur when maintenance workers are manipulating live equipment for testing or repair and accidentally cause a fault. Improper tools, improper electrical equipment, corrosion of equipment, improper work techniques and lack of training are just some of the events that can lead to a devastating arc flash or arc blast.

ARC FLASH COMPLIANCE

There are 4 main regulations that govern electrical safety & arc flash:

- 1. OSHA Standards 29CFR, Part 1910. Occupational Safety and Health Standards. 1910 sub part S (electrical) Standard number 1910.333 specifically addresses Standards for Work Practices and references NFPA 70E. OSHA 29CFR 1910.335 (a) (1)(i) requires the use of protective equipment when working where a potential electrical hazard exists and 29CFR 1910.132(d)(1) which requires the employer assess the workplace for hazards and the need for personal protective equipment. OSHA compliance is required by any plant building or facility.
- 2. The National Fire Protection Association (NFPA) Standard 70 2002 "The National Electrical Code" (NEC) contains requirements for warning labels.
- 3. NFPA 70E provides guidance on implementing appropriate work practices that are required to safeguard workers from injury while working on or near exposed electrical conductors or circuit parts that could become energized. Part II 2-1.3.3 regarding Arc Flash Analysis states that a "Flash Hazard Analysis shall be done before a person approaches any exposed electrical conductor or circuit part that has not been placed in an electrical safe work condition". This Arc Flash Hazard Analysis must be done to determine the level of Personal Protection Equipment PPE that a worker must use, and the Arc Flash Boundary in inches along with the incident energy found at each location. Each panel must be marked with an ANSI z535 approved Arc Flash Warning Label.
- 4. The Institute of Electronics and Electrical Engineers (IEEE) 1584 2002 Guide to Performing Arc-Flash Hazard Calculations

copyright © information by: American Trainco, Inc. http://www.martinarcflash.com

OSHA

Wiha tools assists with compliance of OSHA 29CFR 1910 (Sub Parts electrical standard)

Wiha Insulated Wrenches							
	Description	Page					
—	Insulated Open End Spanners	4-5					
	Insulated Gear Wrenches	6					
I	Ins. Offset Ring Wrenches	7					

Wiha Insulated Adjustable Wrenches

Page

Description

	Description	ı ugc
P	Insulated Adjustable Wrenches 8.0, 10.0, 12.0, 15.0"	8

Wiha Insulated L-keys

Description	Page
Insulated L-keys	9

Wiha Insulated 3/8" Hex Drive Bit Sockets

Description	Page
Ins. 3/8" Hex Dr. Bit Sockets	10

Wiha Insulated Electrician's Knives

Description	Page
Insulated Knives	8

Wiha Insulated Socket Accessories

	Description	Page
-	Insulated Sockets 1/4, 3/8, 1	/2" 10-14
-	Insulated Ratchets	10,13,15
	Insulated T-handle	10,13,15
	Insulated Extension Bars	11,13,15

Wiha Insulated Cable Cutters

	Description	Page
6.	Insulated Cable Cutters	15

Toll Free: (800) 346-8274



Insulated Long Nose Pliers

Insulated Round Nose Pliers

Insulated Stripping Pliers

Insulated Pliers Sets

36

36

37

29-33

W	iha Insulated Hacksaw			W	iha Insulated Tools	
	Description	Page			Description	Page
	Insulated Hacksaw	15			Xeno Terminal Block Combination Screwdrivers	26
Wiha I	Insulated Multi-Bit Holders				Insulated TorqueControl Handle & Blade Holder	18
-	Description Insulated Multi-Bit Drivers	Page 18		wiha	Insulated Single-Pole Voltage Detect	26 or
Wih	a Insulated <i>SlimLine</i> Tools		4	•	Insulated Hex Inch/Metric T-handles	17
	Description	Page		0	Insulated Slotted Drivers	23-24
	Insulated SlimLine Handle	19			Insulated Phillips Drivers	23-24
	Insulated SlimLine Blades	19-20	-		Insulated Torx Drivers	26
	Insulated SlimLine Blade Sets	20			Insulated Nut Drivers	25-26
	Insulated SlimLine Drivers	21			Insulated Square Tip Drive	
	Insulated SlimLine Driver Sets	22			Retaining Ring Bit Holder	27
Wił	na Insulated BitFlip Sets				Insulated Tweezers	16
	Description	Page	\A/:I-		-11-4000V-1-Di/0	li a na
	Insulated BitFlip Sets	27	vvin		ated 1000Volt Pliers/Cut	
M/th a los	vale (e.d. Bell, Beat, Beat, C	-1-			Description	Page
Wina ins	sulated Belt Pack Pouch S				nsulated Lineman's Pliers	34
	Description Insulated Belt Pack Pouches	Page 28			nsulated Combination Pliers	34
71-77. ⊕	Pliers & Cutters Pliers/Cutters & Screwdrivers Pliers/Cutters & Multi Bit Set				nsulated Heavy Duty Diagonal Cutters	35
					nsulated Serrated Edge Cable Cutter	35
Wih	a Insulated Inomic Pliers Description	Page			nsulated Bent Nose Pliers	36


37



Insulated Inomic Pliers

Inomic Combo Pliers Inomic Long Nose Pliers

Inomic Diagonal Cutters





Wiha Insulated Open-End Wrenches

Angled 15°





≙1000Volt

20190	14 Piece I	14 Piece Insulated Inch Open End Wrench Set								
Item		0	OAL		0	OAL	₩.			
No.		Inch	Inch		Inch	Inch	lbs.			
20190	20133	5/16	3.9	20142	3/4	7.0	5.70			
	20135	3/8	4.1	20144	13/16	7.5				
	20136	7/16	4.6	20145	7/8	7.6				
	20137	1/2	5.5	20146	15/16	7.9				
	20138	9/16	5.7	20147	1	8.4				
	20140	5/8	6.2	20148	1-1/16	9.2				
	20141	11/16	6.5	20149	1-1/8	9.1				



20091	15 Piece Ir	15 Piece Insulated Metric Open End Wrench Set									
Item		O MM	OAL		O MM	OAL	₹,				
No.		mm	mm		mm	mm	lbs.				
20091	20006	6.0	97	20014	14	150	3.0				
	20007	7.0	98	20015	15	151					
	20008	8.0	104	20016	16	164					
	20009	9.0	108	20017	17	162					
	20010	10.0	107	20019	19	178					
	20011	11.0	118	20022	22	196					
	20012	12.0	129	20024	24	211					
	20013	13.0	137								



≙1000Volt

20192	8 Piece Insulated Inch Open End Wrench Set								
Item		0	OAL		0	OAL	← →		
No.		Inch	Inch		Inch	Inch	lbs.		
20192	20133	5/16	3.9	20138	9/16	5.7	1.59		
	20135	3/8	4.1	20140	5/8	6.2			
	20136	7/16	4.6	20141	11/16	6.5			
	20137	1/2	5.5	20142	3/4	7.0			



≙1000Volt

20093	8 Piece Insulated Metric Open End Wrench Set								
Item		O MM	OAL		O MM	OAL	£-3		
No.		mm	mm		mm	mm	lbs.		
20093	20006	6.0	97	20013	13.0	137	1.4		
	20007	7.0	98	20014	14.0	150			
	20008	8.0	104	20017	17.0	162			
	20010	10.0	107	20019	19.0	178			

Toll Free: (800) 346-8274

☆1000Volt

SHOP NOW



Inch Open-End Wrenches, With Insulated Handle
Insulation According to VDE Specification 0680 and EN/IEC 60900,
DIN 7446 and CSA, up to 1000 Volt. Individually Tested.

Chrome-vanadium steel, hardened, Angled 15°.

Cili Oille-va	mauium Si	eei, iiai	ueneu.	Aligieu	J.	
Item	0	OAL	OAL	•••		
No.	Inch	mm	Inch	lbs.	pkg.	
20131	1/4	87.5	3.4	.04	1	
20133	5/16	100	3.9	.05	1	
20135	3/8	105	4.1	.09	1	
20136	7/16	117	4.6	.09	1	
20137	1/2	140	5.5	.15	1	
20138	9/16	146	5.7	.15	1	
20140	5/8	158	6.2	.20	1	
20141	11/16	165	6.5	.23	1	
20142	3/4	178	7.0	.33	1	
20144	13/16	191	7.5	.42	1	
20145	7/8	192	7.6	.44	1	
20146	15/16	201	7.9	.51	1	
20147	1	213	8.4	.61	1	
20148	1-1/16	233	9.2	.79	1	
20149	1-1/8	233	9.2	.77	1	

^{*} Lengths are +/- 5% due to coating process



20134	13 Fiece i	nsuiai	ea men	open ⊑na	wrenci	ı set	
In Tool Bo	ox Tray						
Item		0	OAL		0	OAL	<u></u>
No.		Inch	Inch		Inch	Inch	lbs.
20194	20131	1/4	3.4	20141	11/16	6.5	4.90
	20133	5/16	3.9	20142	3/4	7.0	
	20135	3/8	4.1	20144	13/16	7.5	
	20136	7/16	4.6	20145	7/8	7.6	
	20137	1/2	5.5	20146	15/16	7.9	
	20138	9/16	5.7	20147	1	8.4	
	20140	5/8	6.2				



Metric Open-End Wrenches, With Insulated Handle
Insulation According to VDE Specification 0680 and EN/IEC 60900,
DIN 7446 and CSA, up to 1000 Volt. Individually Tested.

Chrome-vanadium steel, hardened. Angled 15°.

Item	MM	OAL	OAL	•••		
No.	mm	mm	Inch	lbs.	pkg.	
20006	6.0	97	3.8	.04	1	
20007	7.0	98	3.9	.05	1	
20008	8.0	104	4.1	.07	1	
20009	9.0	108	4.3	.07	1	
20010	10.0	107	4.2	.08	1	
20011	11.0	118	4.6	.11	1	
20012	12.0	129	5.1	.11	1	
20013	13.0	137	5.4	.19	1	
20014	14.0	150	5.9	.19	1	
20015	15.0	151	5.9	.17	1	
20016	16.0	164	6.5	.22	1	
20017	17.0	168	6.4	.24	1	
20018	18.0	173	6.8	.41	1	
20019	19.0	178	7.0	.32	1	
20020	20.0	190	6.9	.36	1	
20022	22.0	196	7.7	.39	1	
20024	24.0	211	8.3	.58	1	
20027	27.0	218	8.6	.68	1	
20030	30.0	235	9.3	.97	1	
20032	32.0	237	9.3	1.01	1	



20196 13 Pc. Insulated Metric Open End Wrench Set In Tool Box Tray Item 0 OAL 0 OAL No. mm mm mm mm 20016 20196 20008 8.0 104 16.0 164 4.90 20010 10.0 107 20017 17.0 168 20011 11.0 118 20018 18.0 173 20012 12.0 129 20019 19.0 178 20013 13.0 137 20022 22.0 196 24.0 211 20014 14.0 150 20024

20015

15.0

151



Wiha Insulated Ratchet Wrenches





☆1000Volt

213 Inch Insulated Ratchet Wrenches, With Insulated Handle Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt. Individually Tested.

Blade chrome-vanadium steel, hardened.

			,		
Item	0	OAL	OAL	←	
No.	Inch	mm	Inch	lbs.	pkg.
21325	3/8	140	5.5	.14	1
21327	7/16	143	5.6	.15	1
21329	1/2	154	6.1	.18	1
21331	9/16	162	6.4	.22	1
21333	5/8	177	7.0	.30	1
21335	3/4	209	8.2	.46	1



\pm 1000Volt

212 Metric Insulated Ratchet Wrenches, With Insulated Handle Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt. Individually Tested.

Blade chrome-vanadium steel, hardened.

Item	○ MM	OAL	OAL	<u></u>	
No.	mm	mm	Inch	lbs.	pkg.
21208	8.0	125	4.9	.08	1
21210	10.0	140	5.5	.12	1
21212	12.0	150	5.9	.18	1
21213	13.0	152	6.0	.18	1
21214	14.0	163	6.4	.22	1
21217	17.0	193	7.6	.38	1
21219	19.0	210	8.3	.45	1





21391	6 Piece Inch Ins	ulated	Ratchet	Wrenches	Set
Item	0	OAL		0	OA

Item		0	OAL		0	OAL	
No.		Inch	Inch		Inch	Inch	lbs.
21391	21325	3/8	5.5	2133	1 9/16	6.4	1.95
	21327	7/16	5.6	2133	3 5/8	7.0	
	21329	1/2	6.1	2133	5 3/4	8.2	






90	7 Piece Metric Insulated Ratchet Wrenches Se	ŧ

21230	7 1 1000 11	101110	Juliator	a itut			,5 001	
Item		O MM	OAL			O MM	OAL	
No.		mm	mm			mm	mm	lbs.
21290	21208	8.0	4.9		21214	14.0	6.4	2.10
	21210	10.0	5.5		21217	17.0	7.6	
	21212	12.0	5.9		21219	19.0	8.3	
	21213	13.0	6.0					
				•				

Wiha Insulated Deep Offset Ring Wrenches





210 Insulated Metric Offset Ring Wrenches, Insulation According to EN/IEC 60900, ISO 3110 Specification, Up To 1000 Volt.

Individually Tested. Blade Chrome-Vanadium steel, hardened.

Item	⊘ MM	OAL	OAL	↓	
No.	mm	mm	Inch	lbs.	pkg.
21008	8.0	159	6.3	.16	1
21009	9.0	159	6.3	.18	1
21010	10.0	171	6.8	.20	1
21011	11.0	178	7.0	.22	1
21012	12.0	191	7.5	.30	1
21013	13.0	194	7.6	.30	1
21014	14.0	203	8.0	.34	1
21015	15.0	203	8.0	.34	1
21017	17.0	219	8.6	.44	1
21019	19.0	241	9.5	.52	1
21020	20.0	250	9.8	.58	1
21022	22.0	257	10.1	.64	1
21024	24.0	279	11.0	.90	1
21027	27.0	286	11.3	.96	1
21030	30.0	311	12.3	1.28	1
21032	32.0	318	12.5	1.38	1





${\hat \simeq}$ 1000Volt

21093	15 Piece Metric Insulated Offset Ring Wrenches Set	
-------	--	--

-	- · · · · · · · · · · · · · · · · · · ·
Item No.	
21093	Metric:
	8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0, 17.0,
lbs. 8.70	19.0, 22.0, 24.0, 27.0, 30.0, 32.0mm



21095	8 Piece Metric Insulated Offset Ring Wre	nches Set
Item No.	Metric:	₽
21095	10.0, 11.0, 12.0, 13.0, 14.0, 15.0,	lbs.
	17.0, 19.0mm	3.20



210	Insulated Inch Off	set Ring Wr	renches
Item	0	₽ **	
No.	Inch	lbs.	pkg.
21040	1/4	.16	1
21042	5/16	.18	1
21044	3/8	.20	1
21046	7/16	.22	1
21048	1/2	.30	1
21050	9/16	.30	1
21052	5/8	.34	1
21054	11/16	.34	1
21056	3/4	.44	1
21057	25/32	.58	1
21058	13/16	.52	1
21060	7/8	.64	1
21062	15/16	.90	1
21064	1.0	.96	1
21066	1-1/16	1.28	1
21068	1-1/4	1.38	1



21094 15 Piece Inch Insulated Offset Ring Wrenches Set

Item No.

21094 Inch:

1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4,

Ibs. 8.70 13/16, 7/8, 15/16, 1, 1-1/16, 1-1/4"





21096	8 Piece Inch Insulated Offset Ring Wrenches Set					
Item No.	Inch:	₽				
21096	5/16, 3/8, 7/16, 1/2, 9/16,	lbs.				
	5/8, 11/16, 3/4"	3.20				



Wiha Insulated Adjustable Wrenches



76208 Insulated 8" Adjustable Wrench

Insulation According to ASTM, EN/IEC, NFPA, CSA and ISO
Specification, up to 1000 Volt. Individually Tested. Etched on scale for pre-setting size. Slip guard handle for added protection.

Item	OAL	OAL	Capacity	•••	
No.	Inch	mm	Opening	lbs.	pkg.
76208	8.0	200	1"	.7	1

\uparrow 1000Volt

76210 Insulated 10" Adjustable Wrench

Insulation According to ASTM, EN/IEC, NFPA, CSA and ISO Specification, up to 1000 Volt. Individually Tested. Etched on scale for pre-setting size. Slip guard handle for added protection.

Item	OAL	OAL	Capacity	-		
No.	Inch	mm	Opening	lbs.	pkg.	
76210	10.0	250	1-1/4"	1.4	1	

76212 Insulated 12" Adjustable Wrench

Insulation According to ASTM, EN/IEC, NFPA, CSA and ISO Specification, up to 1000 Volt. Individually Tested. Etched on scale for pre-setting size. Slip guard handle for added protection.

Item	OAL	OAL	Capacity	←	
No.	Inch	mm	Opening	lbs.	pkg.
76212	12.0	300	1-1/2"	1.9	1

☆1000Volt

76215 Insulated 15" Adjustable Wrench

Insulation According to ASTM, EN/IEC, NFPA, CSA and ISO Specification, up to 1000 Volt. Individually Tested. Etched on scale for pre-setting size. Slip guard handle for added protection.

Item	OAL	OAL	Capacity	- →	
No.	Inch	mm	Opening	lbs.	pkg.
76215	15.0	380	1-11/16"	2.8	1



76290 3 Pc. Insulated Adjustable Wrenches Etched on scale for pre-setting size. Slip guard handle for added protection.

Item No. 76290	Set includes the following:	
↓ Ibs. 4.0	8.0", 10.0", 12.0" Adjustable Pliers	

SHOP NOW

Wiha Insulated Electrician's Knives



Each tool individually tested to 10,000 volts & rated to 1000 Volt ac or 1500 Volt dc



☆1000Volt

Insulated Electrician's Cable Stripping Knife, With Insulated Handle, Insulation According To VDE Specification, Up To 1000 Volt. Individually Tested.

Blade tool steel, hardened, molded directly on. Cover included.

Item	Blade	e OAL	OAL	<i>-</i>	
No.	mm	mm	Inch	lbs. pl	κ g .
15000	50	216	8.5	.30 1	



☆1000Volt

Insulated Electrician's Cable Stripping Knife, With
Insulated Handle, Insulation According To VDE Specification,
Up To 1000 Volt. Individually Tested. Straight, partly insulated,
strong blade. Insulation molded directly on. Cover included.

Item	Blade	OAL	OAL			
No.	mm	mm	Inch	lbs.	pkg.	
15003	50	230	9.0	.23	1	



\pm 1000Volt

Insulated Stripping Knife, With Insulated Handle
Insulation According To VDE Specification, Up To 1000 Volt.
Individually Tested. Blade tool steel, hardened. Insulation molded directly on. Hooked cutting edge, half-round ground. Cover included.

Item	Blade	OAL	OAL	•		
No.	mm	mm	Inch	lbs.	pkg.	
15050	35	222	8.75	.22	1	

Toll Free: (800) 346-8274

wiha

SHOP NOW

Wiha Insulated Hex L-keys





Inch Insulated Hex L-keys, With Insulated Handle
Insulation According to IEC 60900 Specification, Up To 1000 Volt.
Individually Tested. Blade chrome-vanadium steel, hardened.

Item	0	OAL	OAL	←	_
No.	Inch	mm	Inch	lbs.	pkg.
13670	1/16	79	3.1	.05	1
13671	5/64	84	3.3	.05	1
13672	3/32	89	3.5	.05	1
13673	7/64	94	3.7	.06	1
13663	1/8	104	4.1	.06	1
13665	5/32	104	4.1	.06	1
13666	3/16	134	5.3	.10	1
13667	7/32	134	5.3	.12	1
13668	1/4	134	5.3	.16	1
13669	5/16	144	5.7	.24	1
13662	3/8	234	9.2	.51	1
13664	1/2	234	9.2	.77	1



136 Metric Insulated Hex L-keys, With Insulated Handle
Insulation According to IEC 60900 Specification, Up To 1000 Volt.
Individually Tested. Blade chrome-vanadium steel, hardened.

martiaac	marriadany rested. Blade ememe variation steel, naraemea.					
Item	○ MM	OAL	OAL		_	
No.	mm	mm	Inch	lbs.	pkg.	
13650	1.5	100	3.9	.09	1	
13651	2.0	105	4.1	.09	1	
13652	2.5	115	4.5	.09	1	
13653	3	130	5.1	.10	1	
13654	4	120	4.7	.10	1	
13655	5	140	5.5	.10	1	
13656	6	140	5.5	.13	1	
13658	8	150	5.9	.24	1	
13659	10	220	8.7	.51	1	
13657	12	260	10.2	.77	1	





13690	8 Piece Insulated Inch Hex L-key Set							
Item		0	OAL		0	OAL	←	
No.		Inch	Inch		Inch	Inch	lbs.	
13690	13663	1/8	4.1	13668	1/4	5.3	2.17	
	13665	5/32	4.1	13669	5/16	5.7		
	13666	3/16	5.3	13662	3/8	9.2		
	13667	7/32	5.3	13664	1/2	9.2		

13691	7 Piece Inst	ulated	Metric	Hex	L-key			0Volt
Item		O MM	OAL			O MM	OAL	₹
No.		mm	mm			mm	mm	lbs.
13691	13653	3.0	130	·	13658	8.0	150	2.07
	13654	4.0	120	·	13659	10.0	220	
	13655	5.0	140		13657	12.0	260	
	13656	6.0	140					



_							
13693	10 Piece In	sulate	ed Metri	Hex L-key	Set	\pm 100	0Volt
Item		O MM	OAL		O MM	OAL	← →
No.		mm	mm		mm	mm	lbs.
13693	13650	1.5	100	13655	5.0	140	2.26
	13651	2.0	105	13656	6.0	140	
	13652	2.5	115	13658	8.0	150	
	13653	3.0	130	13659	10.0	220	
	13654	4.0	120	13657	12.0	260	

	1000Volt						
13694	12 Piece Ins	et	≙100	0Volt			
Item		0	OAL		0	OAL	₽
No.		Inch	Inch		Inch	Inch	lbs.
13694	13670	1/16	3.1	13666	3/16	5.3	2.40
	13671	5/64	3.3	13667	7/32	5.3	
	13672	3/32	3.5	13668	1/4	5.3	
	13673	7/64	3.7	13669	5/16	5.7	
	13663	1/8	4.1	13662	3/8	9.2	
	13665	5/32	4.1	13664	1/2	9.2	

SHOP NOW

Wiha Insulated Hex Bit Sockets



\pm 1000Volt

318 Insulated 3/8" Drive Sockets - Insulation according to EN/IEC 60900, DIN 7448 Specification, Up To 1000 Volt.

Individually Tested. Chrome-vanadium steel, forged, oil-hardened.

Item		OAL	<u></u>		
No.	Inch	Inch	lbs.	pkg.	
31805	3/16	3.1"	.13	1	
31807	7/32	3.1"	.14	1	
31809	1/4	3.1"	.14	1	
31811	5/16	3.1"	.16	1	
31813	3/8	3.1"	.18	1	
31815	7/16	3.1"	.20	1	
31817	1/2	3.1"	.22	1	

^{*}Sockets must be used with insulated ratchets & extensions





 \triangle 1000Volt

31890 7 Pc. Insulated 3/8" Drive Socket Set - Inch

CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.

Item No. 31890 Set includes the following:

U lbs. 1.7 3/16, 7/32, 1/4, 5/16, 3/8, 7/16, 1/2"

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70 $^{\circ}$ C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.

Wiha Insulated 1/4" Sockets & Sets

Inch -6 Point





☆1000Volt

Insulated 1/4" Drive Sockets - 6 Point, Insulation According To ASTM F-1505-01, DIN 7448 & CSA Specification, Up To 1000

Volt. In	dividually T	ested. Ch	nrome-vanadium steel, forged, oil-hardene
Item		- →	
No.	Inch	lbs.	pkg.
31336	3/16	.03	1
31337	7/32	.03	1
31338	1/4	.03	1
31339	9/32	.04	1
31340	5/16	.04	1
31341	11/32	.05	1
31342	3/8	.05	1
31343	7/16	.06	1
31344	1/2	.07	1
31345	9/16	.07	1

^{*}Sockets must be used with insulated ratchets & extensions

Metric -6 Point





\triangle 1000Volt

Insulated 1/4" Drive Sockets - 6 Point, Insulation According To ASTM F-1505-01, DIN 7448 & CSA Specification, Up To 1000 Volt. Individually Tested. Chrome-vanadium steel, forged, oil-hardened.

Item		↓	_
No.	mm	lbs.	pkg.
31326	5.0	.03	1
31327	6.0	.03	1
31328	7.0	.03	1
31329	8.0	.04	1
31330	9.0	.04	1
31331	10.0	.05	1
31332	11.0	.05	1
31333	12.0	.06	1
31334	13.0	.06	1
31335	14.0	.07	1

^{*}Sockets must be used with insulated ratchets & extensions



☆1000Volt

12851 Insulated 1/4" Drive Ratchet, EN/IEC 60900 & CSA

Item		OAL	OAL	<u> </u>		
No.	Inch	mm	Inch	lbs.	pkg.	
12851	1/4"	140	5.5	.28	1	

Wiha Insulated 1/4" Sockets & Sets





∕∷1000Volt

31390 13 Piece Insulated 1/4" Drive Socket Set - Inch

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900.

Item No. 31390	Set includes the following:
	3/16, 7/32, 1/4, 9/32, 5/16, 11/32,
lbs.	3/8, 7/16, 1/2, 9/16"
1.39	1/4" x 50mm Extension Bar
	1/4" x 100mm Extension Bar
	1/4" Ratchet - 140mm





∕☆1000Volt

31391 13 Piece Insulated 1/4" Drive Socket Set - Metric

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900

Cv steer, lorged, i	oli-nardened sockets. Insulated after EN/IEC 60900.
Item No. 31391	Set includes the following:
↓	5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm
lbs.	1/4" x 50mm Extension Bar
1.41	1/4" x 100mm Extension Bar
	1/4" Ratchet - 140mm



31394 11 Piece Insulated 1/4" T-handle & Socket Set - Inch

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900			
Item No. 31394	Set includes the following:		
↓	3/16, 7/32, 1/4, 9/32, 5/16, 11/32,		
lbs.	3/8, 7/16, 1/2, 9/16"		
1.40	Insulated 1/4" T-handle		



≙1000Volt

31395 11 Piece Insulated 1/4" T-handle & Socket Set - Metric

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900.

Item No. 31395 Set includes the following: **-**5, 6, 7, 8, 9, 10, 11, 12, 13, 14mm

Insulated 1/4" T-handle lbs. 1.40

Each tool individually tested to 10,000 volts & certified to 1000 Volt ac or 1500 Volt dc

SHOP NOW

Wiha Insulated 1/4" Socket accessories



29006 Insulated 1/4" Drive T-handle, With Insulated Handle Insulation according to EN/IEC 60900 & CSA specification, up to 1000 Volt. Individually Tested. Blade CV steel, hardened.

Item	○ MM	OAL	OAL	<u></u>		
No.	Inch	mm	Inch	lbs.	pkg.	
29006	1/4	160	6.2"	.57	1	



☆1000Volt

128 Insulated 1/4" Extension Bars, ASTM F-1505-01,

EN/IEC 60900 & CSA Chrome-Vanadium steel.						
Item		OAL	OAL	-		
No.	Inch	mm	Inch	lbs.	pkg.	
12854	1/4"	50	2.0	.08	1	
12855	1/4"	100	3.9	.12	1	

SHOP NOW

Wiha Insulated 3/8" Sockets & Sets



☆1000Volt

314 Insulated 3/8" Drive Sockets - Insulation according to EN/IEC 60900, DIN 7448 & CSA specification, up to 1000 Volt.

Individually Tested. CV steel, forged, oil-hardened.

marriadany		O . O.O.,	lorgoa, on riaraorioa.
Item		←	
No.	Inch	lbs.	pkg.
31425	1/4	.07	1
31428	9/32	.07	1
31429	5/16	.07	1
31430	11/32	.07	1
31431	3/8	.08	1
31432	7/16	.08	1
31433	1/2	.10	1
31434	9/16	.10	1
31435	5/8	.10	1
31436	11/16	.13	1
31437	3/4	.14	1
31438	13/16	.17	1
31439	7/8	.18	1

^{*}Sockets must be used with insulated ratchets & extensions



\triangle 1000Volt

Insulated 3/8" Drive Sockets - Metric Insulation according to VDE, EN/IEC 60900, DIN 7448 & CSA specification, up to 1000 Volt. Individually Tested. Chrome-vanadium steel, forged, oil-hardened.

			variadiam otooi, lorgod, on mardonod.	
Item		←		
No.	mm	lbs.	pkg.	
31506	6.0	.07	1	
31507	7.0	.07	1	
31508	8.0	.07	1	
31509	9.0	.07	1	
31510	10.0	.07	1	
31511	11.0	.08	1	
31512	12.0	.10	1	
31513	13.0	.10	1	
31514	14.0	.10	1	
31515	15.0	.10	1	
31516	16.0	.10	1	
31517	17.0	.11	1	
31518	18.0	.12	1	
31519	19.0	.14	1	
31520	20.0	.15	1	
31521	21.0	.17	1	
31522	22.0	.18	1	
31524	24.0	.26	1	

^{*}Sockets must be used with insulated ratchets & extensions

Wiha Insulated 3/8" Sockets & Sets



31493 10 Piece	e Insulated 3/8" Drive Socket Set - Inch
CV steel, forged, o	oil-hardened sockets. Insulated to EN/IEC 60900.
Item No. 31493	Set includes the following:
	5/16, 3/8, 7/16, 1/2,
lbs.	9/16, 5/8, 11/16, 3/4"
2.50	3/8" x 125mm Extension Bar
	3/8" Ratchet - 280mm



31590	10 Piece Insulated 3/8" Drive Socket Set - Metric		
CV steel,	forged,	oil-hardened sockets.	Insulated to EN/IEC 60900.
Item No.	31590	Set includes the fo	ollowing:

Item No. 31590	Set includes the following:
	8, 10, 11, 12, 13, 14, 17, 19mm
lbs.	3/8" x 125mm Extension Bar
2.50	3/8" Ratchet - 280mm



31491	16 Piece Insulated 3/8" Drive Socket Set - Inch/Metric			
CV steel	, forged, o	I-hardened sockets.	Insulated to EN/IEC 60900.	
Item No.	31491	Set includes the fo	ollowing:	

01701	•
₽ **	5/16, 3/8, 7/16, 1/2,
lbs.	9/16, 5/8, 11/16, 3/4"
2.01	8, 10, 11, 12, 13, 14, 17, 19mm

Wiha Insulated 3/8" Sockets & Sets



24 Piece Insulated 3/8" Drive Socket Set - Inch

CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.					
Item No.	1495 Set includes the following:				
	1/4, 9/32, 5/16, 11/32, 3/8, 7/16				
	1/2, 9/16, 5/8,11/16, 3/4" Sockets				
lbs.	3/8" x 125mm Extension Bar				
9.07	3/8" x 250mm Extension Bar				
3/8" Ratchet - 190mm					
Insulated Electrician's Knife - 50mm					
Slotted: 3.5, 4.5, 6.5mm					
	Phillips: 1, 2, 3				
	6.3" Long Nose Pliers				
	8.0" Combo Pliers				
	6.3" Diagonal Cutters				

^{*}Sockets must be used with insulated ratchets & extensions



24 Piece Insulated 3/8" Drive Socket Set - Metric

CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.

Item No. 31592		Set includes the following:	
		6, 7, 8, 9, 10, 11, 12,	
←		13, 14, 17, 19mm Sockets	
lbs.	3/8" x 1	25mm Extension Bar	
9.08	3/8" x 250mm Extension Bar		
	3/8" Rat	chet - 190mm	
Insulate		d Electrician's Knife - 50mm	
Slotted		: 3.5, 4.5, 6.5mm	
Phillips		: 1, 2, 3	
	6.3" Lor	ng Nose Pliers	
	8.0" Cor	mbo Pliers	
	6.3" Dia	gonal Cutters	

*Sockets must be used with insulated ratchets & extensions



≙1000Volt

31496 10 Piece Insulated 3/8" T-handle & Socket Set - Inch

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900.

Item No	. 31496	Set includes the following:
←		5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4"
lbs.		3/8" x 125mm Extension Bar
2.47		Insulated 3/8" T-handle
31595	10 Piece	Insulated 3/8" T-handle & Socket Set - Metric

CV steel, forged, oil-hardened sockets. Insulated after EN/IEC 60900. Set includes the following:

item No. 31595	Set includes the following:
- →	8, 10, 11, 12, 13, 14, 17, 19mm
lbs.	3/8" x 125mm Extension Bar
2.47	Insulated 3/8" T-handle

Wiha Insulated 3/8" Socket accessories



≙1000Volt

12852 Insulated 3/8" Drive Ratchet, EN/IEC 60900

Chrome-Vanadium steel. Reversible.

Item		OAL	OAL	•	_
No.	Inch	mm	Inch	lbs.	pkg.
12852	3/8"	190	7.5	.93	1



128 Insulated 3/8" Extension Bars, EN/IEC 60900

Chrome-Vanadium steel.

Item		OAL	OAL		-
No.	Inch	mm	Inch	lbs.	pkg.
12856	3/8"	125	4.9	.41	1
12857	3/8"	250	9.8	.57	1



1000Volt Insulated 3/8" Drive T-handle Or Breaker Bar

Insulation according to EN/IEC 60900 specification, up to 1000 Volt Rated. Individually Tested. Blade chrome-vanadium steel, hardened.

○ MM	OAL	OAL		
Inch	mm	Inch	lbs.	pkg.
3/8	200	7.9"	.55	1
3/8	225	9.0"	.68	1
	Inch 3/8	Inch mm 3/8 200	3/8 200 7.9"	Inch mm Inch lbs. 3/8 200 7.9" .55



Wiha Insulated 1/2" Sockets & Sets



☆1000Volt

317 Insulated 1/2" Drive Sockets - Insulation According to ASTM F-1505-01, DIN 7448 & CSA Specification, Up To 1000 Volt.

Individually Tested. CV steel, forged, oil-hardened. Item

Item		•	
No.	Inch	lbs.	pkg.
31703	5/16	.16	1
31704	11/32	.16	1
31705	3/8	.16	1
31707	7/16	.16	1
31708	1/2	.16	1
31709	9/16	.17	1
31710	5/8	.19	1
31712	11/16	.19	1
31713	3/4	.21	1
31714	13/16	.23	1
31715	7/8	.27	1
31716	15/16	.35	1
31718	1	.33	1
31720	1-1/8	.44	1
31722	1-1/4	.58	1

^{*}Sockets must be used with insulated ratchets & extensions



Individually Tested



≙1000Volt

Insulated 1/2" Drive Sockets - Metric Insulation According to VDE, DIN 7448 & CSA Specification, Up To 1000 Volt.

Item		•••	
No.	mm	lbs.	pkg.
31608	8.0	.15	1
31609	9.0	.15	1
31610	10.0	.16	1
31611	11.0	.16	1
31612	12.0	.16	1
31613	13.0	.17	1
31614	14.0	.17	1
31615	15.0	.17	1
31616	16.0	.19	1
31617	17.0	.19	1
31618	18.0	.20	1
31619	19.0	.21	1
31620	20.0	.25	1
31621	21.0	.25	1
31622	22.0	.28	1
31623	23.0	.29	1
31624	24.0	.30	1
31626	26.0	.37	1
31627	27.0	.41	1
31628	28.0	.44	1
31630	30.0	.51	1
31632	32.0	.55	1

^{*}Sockets must be used with insulated ratchets & extensions

Wiha Insulated 1/2" Sockets & Sets



oxtime 1000 m Volt

31790	24 Piece Insulated 1/2" Drive Socket Set - Inch
CV steel,	forged, oil-hardened sockets. Insulated to EN/IEC 60900.
Item No.	Set includes the following:
31790	3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1" Sockets
-	1/2" x 125mm Extension Bar
lbs.	1/2" x 250mm Extension Bar
11.41	1/2" Ratchet - 260mm
	Insulated Electrician's Knife - 50mm
	Slotted: 3.5, 4.5, 6.5mm & Phillips: 1, 2, 3
	6.3" Long Nose Pliers
	8.0" Combo Pliers
	6.3" Diagonal Cutters

Each tool individually tested to 10,000 volts & certified to 1000 Volt ac or 1500 Volt dc



Metric 31691 2

31691 24 Piece Insulated 1/2" Drive Socket Set - Metric CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.

 Item No.
 Set includes the following:

 31691
 8, 9, 10, 12, 13, 14, 15, 17, 19, 22, 24mm Sockets

 ★ ★ ★ 1/2" x 125mm Extension Bar

 Ibs.
 1/2" x 250mm Extension Bar

 11.39
 1/2" Ratchet - 260mm

Insulated Electrician's Knife - 50mm **Slotted:** 3.5, 4.5, 6.5mm & **Phillips:** 1, 2, 3 6.3" Long Nose Pliers

8.0" Combo Pliers 6.3" Diagonal Cutters



12326 Insulated 1/2" Drive Breaker Bar, IEC/EN 60900 & CSA

Chrome-Vanadium steel.

Item		OAL	OAL	↓	
No.	Inch	mm	Inch	lbs.	pkg.
12326	1/2"	250	9.8	1.04	1

Toll Free: (800) 346-8274

SHOP NOW

Wiha Insulated 1/2" Socket accessories



12853 Insulated 1/2" Drive Ratchet, IEC/EN 60900 & CSA

Chrome-Vanadium steel Reversible

000		0.00			
Item		OAL	OAL	<u></u>	
No.	Inch	mm	Inch	lbs.	pkg.
12853	1/2"	260	10.2	1.55	1



\pm 1000Volt

 \pm 1000Volt

128 Insulated 1/2" Extension Bars, EN/IEC 60900 & CSA

Chrome-vanadium steel

CHIOHIE-V	anaulun	i Sieei.			
Item		OAL	OAL	•	_
No.	Inch	mm	Inch	lbs.	pkg.
12858	1/2"	125	4.9	.45	1
12859	1/2"	250	9.8	.91	1



Insulated 1/2" Drive T-handle, With Insulated Handle Insulation according to EN/IEC 60900 & CSA Specification, Up To 1000 Volt. Individually Tested. Blade VC steel, hardened.

Item	O MM	OAL	OAL		_
No.	Inch	mm	Inch	lbs.	pkg.
29012	1/2	200	7.9"	.68	1

SHOP NOW

Uses standard 12" blade



19767 Hacksaw, With Insulated Handle

Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

Item	OAL	OAL	•••			
No.	mm	Inch	lbs.	pkg.		
19767	457mm	18.0"	1.92	1		

SHOP NOW

Wiha Insulated Cable Cutters



\pm 1000Volt

11950 Cable Cutter, With Insulated Handle Insulation According to EN/IEC 60900, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

Blade alloyed tool steel. Induction hardened.

Item	OAL	OAL	Capa	city		
No.	mm	Inch	mm	Inch	lbs.	pkg.
11950	500	19.6	12	1/2"	3.0	1

For cutting multi strand aluminum & copper cables



☆1000Volt

40800 Large Capacity Cable Cutter, With Insulated Handle Insulation According to EN/IEC 60900, ASTM F-1505 & CSA Specification, Up to 1000 Volt. Individually Tested.

Easy cutting blades, dropped forged, oil hardened. Cuts cable diameters up to 50mm. Not to be used on steel rods.

Item	OAL	OAL	Capa	city	- →		
No.	mm	Inch	mm	Inch	lbs.	pkg.	
40800	800	31.5	50	2"	8.0	1	



For cutting solid aluminum, copper & medium hard wires

SHOP NOW

\triangle 1000Volt

29250 End Cutters, With Insulated Handle. Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification.

Individually Tested. Blade alloyed tool steel. Induction hardened.

Item	OAL	OAL	Capacity	←	_
No.	mm	Inch	mm	lbs.	pkg.
29250	250	10	7/8"	1.1	1

SHOP NOW



29240 Waterpump Pliers, With Insulated Handle Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

Box joint. Chrome-vanadium steel, drop forged, oil hardened.

Item	OAL	OAL	Capacity	+	
No.	mm	Inch	mm	lbs.	pkg.
29240	240	9.5	7/8"	1.1	1

SHOP NOW



\pm 1000Volt

116 Waterpump Pliers, With Insulated Handle Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

Chrome-vanadium steel, drop forged, oil hardened.

Item	OAL	OAL	•			
No.	mm	Inch	lbs.	pkg.		
11625	250	10.0"	1.2	1		
11630	300	12.0"	1.8	1		

Wiha Insulated Ratcheting Cable Cutters



119 High Voltage Double-Insulated Ratcheting Cable Cutters Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.

High leverage ratchet cable cutter with shear type blades cuts stranded and flexible copper and aluminum cable. Not for use on steel. Features built in safety release in all cutting positions, and high-visibility comfort grip handles.

Item	OAL	OAL	up to	Inch		←		
No.	mm	Inch	MCM	Dia.	Capacity	lbs.	pkg.	
11960	250	10.0"	500	1.25"	32ml	1.58	1	
11975	280	11.0"	750	2.0"	52ml	2.02	1	

SHOP NOW

Wiha Insulated Serrated Tweezers



\triangle 1000Volt

75205 Insulated Serrated Straight Fine Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

Item	OAL	OAL	←	
No.	mm	Inch	lbs.	pkg.
75205	130	5.0	.06	1



\pm 1000Volt

75210 Insulated Serrated Straight Blunt Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

120/214 00000 & OOA Otaliaaras, 10,000 Voit restea						
Item	OAL	OAL	•			
No.	mm	Inch	lbs.	pkg.		
75210	130	5.0	.08	1		



☆1000Volt


75215 Insulated Serrated Straight Blunt Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

,						
Item	OAL	OAL	•	-		
No.	mm	Inch	lbs.	pkg.		
75215	145	6.0	.10	1		

SHOP NOW

Wiha Insulated Serrated Tweezers





\pm 1000Volt

75220 Insulated Serrated Straight Blunt Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

120,211 00000 a 00,1 01a11aa1 au, 10,000 1011 10010a						
Item	OAL	OAL	-			
No.	mm	Inch	lbs.	pkg.		
75220	200	8.0	.18	1		



\pm 1000Volt

75302 Insulated Serrated Angled Fine Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested Item OAL No. lbs. mm Inch pkg. 75302

6.0

145



.08

\pm 1000Volt


75304 Insulated Serrated Angled Blunt Tip Tweezers,

IEC/EN 60900 & CSA Standards, 10,000 Volt Tested

120/214 00000 & OOA Otandards, 10,000 Voit 10sted					
Item	OAL	OAL	<u> </u>	_	
No.	mm	Inch	lbs.	pkg.	
75304	200	8.0	.16	1	

Wiha Insulated T-handles







Inch T-handle, With Wiha-Molded Handle. Insulation
According to ASTM F-1505-01, New VDE Specification 0682/part 201
and EN/IEC 60900, NFPA70E & CSA, ☆ up to 1000Volt. Individually
Tested. Blade CVM steel, hardened. Insulation molded directly onto
blade. Wiha-SoftFinish® handle, multi-component.

Item		=	<u></u>		•	
No.	Inch	Inch	Inch	mm	lbs.	pkg.
33481	5/32	5.9	6.9	176	.09	10
33482	3/16	5.9	6.9	176	.15	10
33483	7/32	5.9	6.9	176	.19	10
33485	1/4	5.9	7.1	176	.20	10
33486	5/16	5.9	7.1	176	.26	10
33487	3/8	5.9	7.1	176	.44	10







According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, ☆ up to 1000Volt. Individually Tested. Blade CVM steel, hardened. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component.

Item		=	=	<u></u>		<u></u>	_
No.	mm	mm	Inch	mm	Inch	lbs.	pkg.
33441	4.0	150	5.9	176	6.9	.09	10
33443	5.0	150	5.9	182	7.1	.15	10
33445	6.0	150	5.9	182	7.1	.18	10
33447	8.0	150	5.9	182	7.1	.26	10
33449	10.0	150	5.9	191	7.5	.46	10



33478	5 Piece Metric T-handle Hex Set	
Item		₽ **•
No.	Metric:	lbs.
33478	4.0, 5.0, 6.0, 8.0, 10.0mm	1.20

 \pm 1000Volt

Wiha Multi-Bit Screwdrivers

Six Tools in One!



Tested to

10,000 Volts Insulation meets EN/IEC 60900

380 Sets Multi-Bit Screwdriver Sets with Wiha Powerhandle, cellulose-acetate, impact resistant. Snap-lock rotatable cap.

Chambered bit holder equipped with transparent selector and 6 bits. 1/4" Bit holder, stainless steel. Shaft chrome-vanadium-molybdenum steel, hardened, chrome-plated. Packaged in clear blister package. Blade Length = 120mm (4.7") Overall Length = 230mm (9")

38006 Slotted/Phillips Multi-Bit Screwdriver

With Wiha Powerhandle and insulated shaft.

	
lbs.	
.39	
	lbs.

38007 Slotted/Phillips/Square Multi-Bit Screwdriver

With Wiha Powerhandle and insulated shaft.

Set includes the following 1/4" bits:	↓	
\$ Slotted Sizes: 6.5, 8.0mm	lbs.	
Phillips Sizes: 1, 2	.41	
C Square Sizes: 1 2		

38025 Magnetic Bit Holder, 1/4" Wiha Powerhandle and insulated shaft. Holder only can hold up to 6 bits.

₩ Ibs. .26

Wiha Insulated TorqueControl Tools

Includes Certificate

1872 | Wiles Torque (Sinte P.S.)

Includes SlimLine blade holder

Insulated TorqueVario-S, With Window Scale Insulation up to 1000 Volt. EN/IEC 60900 EN ISO 6798, BS EN 26789,

ASME B107.14M &CSA, +/- 6% Accuracy. Ergonomic multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained.

Item	Range		=	←	_
No.	Inch lbs.	Increments	mm	lbs.	pkg.
28724	7.5 - 20	.5 Inch lbs	126 - 131	.43	1
28726	10 - 50	2 Inch lbs	133 - 138	.40	1
28727	20 - 70	2 Inch lbs	137 - 142	.69	1

nsulated TorqueVario-S Handle - In Newton Meter Scale

item	Kange		• •	_	
No.	Nm	mm	lbs.	pkg.	
28734	0.6 - 2.0	131	.45	1	
28736	1.0 - 5.0	138	.45	1	
28737	2.0 - 8.0	142	.72	1	

Each TorqueVario handle has unique serial number & certificate of calibration

hinspace 1000Volt

28350 Insulated *Slim*Line Torque Blade Holder

Chrome-vanadium-molybdenum steel. Through hardened black finish. ClicFix quick release holder securely locks bits.

Item		OAL	OAL	<u></u>			
No.	mm	mm	Inch	lbs.	pkg.		
28350	6.0	170	6.7	.02	1		

Wiha Insulated TorqueControl & SlimLine Tool Sets



8 Piece Insulated TorqueControl Set With Slotted & Phillips SlimLine Blades Certified to EN ISO 6798, BS EN 26789,
ASME B107.14M. Set includes Insulated multi-component adjustable
TorqueVario-S handle, 5 SlimLine blades, SlimLine blade holder &
Torque adjustment tool.

- 1	,	
Item N	↓ lbs.	
28791	SlimLine Slotted: 3.0, 4.0, 5.5mm	.87
	SlimLine Phillips: #1, #2	
	28726 - Handle Range 10-50 Inch/lbs.	
	SlimLine Blade Holder	

With Certificate of Calibration



28792 16 Piece Insulated TorqueControl Set With SlimLine Blades

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes Insulated multi-component adjustable TorqueVario-S handle,

13 SlimLine blades, SlimLine blade holder & Torque adjustment tool.

Item No).	↓ lbs.
28792	SlimLine Slotted: 4.0, 5.5, 6.5mm	1.27
	SlimLine Phillips: #1, 2	
	SlimLine Terminal Xeno: #1, 2	
	SlimLine TORX *: T8, T10, T15, T20	
	SlimLine Square: #1, 2	
	28727 - Handle Range 20-70 Inch/lbs.	
	SlimLine Blade Holder	

wiha wiha

SHOP NOW

Wiha Insulated SlimLine Tools



Wiha Insulated SlimLine Handle



Inch lbs.

.15

6.3

pkg.

33% narrower insulation diameter

No.

28301

Size

1/4"

mm


Inch mm


160

2.0



Wiha Insulated SlimLine Blades







Wiha Insulated SlimLine Blades



283 Insulated Xeno Slotted & Phillips SlimLine Blades

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools.

Item	\oplus	===	Slim	Working	Max	Inch/	- →	
No.	Size	mm	Dia.	Length	Nm	lbs.	lbs.	Pkg.
28327	1	90	4.1	2.8"	3.8	33.7	.02	1
28329	2	90	6.1	2.8"	5.5	48.8	.02	1



283 Insulated TORX® SlimLine Blades

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools.

00,0110110		0 4.4.0						
Item	0	===	Slim	Working	Max	Inch/	_	
No.	Size	mm	Dia.	Length	Nm	lbs.	lbs.	Pkg.
28339	T8	90	4.1	2.8"	1.3	11.5	.02	1
28340	T10	90	4.1	2.8"	3.8	33.7	.02	1
28341	T15	90	6.1	2.8"	5.5	48.8	.02	1
28342	T20	90	6.1	2.8"	5.5	48.8	.02	1



283 Insulated Square SlimLine Blades

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools.

Item	0	===	Slim	Working	Max	Inch/	↓	
No.	Size	mm	Dia.	Length	Nm	lbs.	lbs.	Pkg.
28346	1	90	4.1	2.8"	3.8	33.7	.02	1
28347	2	90	6.1	2.8"	5.5	48.8	.02	1



Wiha Insulated SlimLine Blade Sets





≙1000Volt

28391 8 Piece Insulated SlimLine Blade Set

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools. Cushion grip handle with quick release holder to securely

lock blades.	in roll up	o pouch
Itam Na		

Item No	J lbs.	
28391	Slotted: 4.0, 6.5 x 90mm	.45
	Phillips: #1, #2 x 90mm	
	Xeno: #2 x 90mm	
	TORX *: T15, T20 x 90mm	
	28301 - SlimLine Cushion Grip Blade Holder	





≙1000Volt

28390 15 Piece Insulated SlimLine Blade Set

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools. Cushion grip handle with quick release holder to securely

lock blades. In roll up pouch

	400:ap pouc	
Item No).	
28390	Slotted: 3.0, 4.0, 5.5, 6.5 x 90mm	.56
	Phillips: #1, #2 x 90mm	
	Xeno: #1, #2 x 90mm	
	TORX®: T8, T10, T15, T20 x 90mm	
	Square: #1, #2 x 90mm	
	28301 - SlimLine Cushion Grip Blade Holder	





320 Insulated Slotted SlimLine Screwdrivers Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, $\stackrel{\textstyle \leftarrow}{\sim}$ up to 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

			,					
Item	0	0	0	Slim		==	₽	_
No.	mm	Inch	Inch	Dia.	mm	mm	lbs.	Pkg.
32046	3.5	.139	9/64	3.5	100	204	.07	1
32049	4.0	.157	5/32	4.0	100	211	.12	1
32052	4.5	.177	3/16	4.5	125	211	.14	1
32055	5.5	.216	7/32	5.5	125	243	.21	1
32058	6.5	.255	1/4	6.5	150	268	.25	1



307 Insulated Xeno SlimLine Screwdrivers For Terminal Screws Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, $\stackrel{\textstyle \leftarrow}{\sim}$ up to 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	\oplus	Slim	==	===	↓		
No.	Size	Dia.	mm	mm	lbs.	Pkg.	
30746	1	4.5	80	191	.12	1	
30747	2	6.0	100	218	.21	1	



321 Insulated Phillips SlimLine Screwdrivers Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, $\stackrel{\frown}{\sim}$ up to 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	•	Slim	==	===	- →		
No.	Size	Dia.	mm	mm	lbs.	Pkg.	
32145	1	4.5	80	204	.12	1	
32146	2	6.0	100	211	.21	1	



358 Insulated Square SlimLine Screwdrivers Insulation According to ASTM F-1505-01, New VDE Specification 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	0	Slim		==	•••	
No.	Size	Dia.	mm	mm	lbs.	Pkg.
35844	1	4.0	100	218	.12	1
35845	2	4.5	125	243	.19	1



Wiha Insulated SlimLine Screwdriver Sets




11 Piece Insulated SlimLine Slotted, Phillips, Xeno & Square Screwdrivers. Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, up to 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools.

Wiha-SoftFinish® handle, multi-component, cushion grip.

Item		•	==		‡ (
No.		Size	mm		mm	mm	lbs.
32198	Phillips	1	80	Slotted	3.5	100	1.75
	Phillips	2	100	Slotted	4.0	100	
		0	-	Slotted	4.5	125	
	Square	1	100	Slotted	5.5	125	
	Square	2	125	Slotted	6.5	150	
		\oplus	=				
	Xeno	1	80				
	Xeno	2	100				



8 Piece Insulated SlimLine Slotted, Phillips & Square Screwdrivers. Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA,

up to 1000 Volt. Individually Tested to 10,000Volts.

High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item		0			‡0	==	₽
No.		Size	mm		mm	mm	lbs.
32197	Phillips	1	80	Slotted	3.5	100	1.18
	Phillips	2	100	Slotted	4.0	100	
		0		Slotted	4.5	125	
	Square	1	100	Slotted	5.5	125	
	Square	2	125				



High quality CV steel, through hardened. *SlimLine* blades have up to 33% narrower insulation diameter then standard insulated tools. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item		•	==		‡0	==	
No.		Size	mm		mm	mm	lbs.
32196	Phillips	1	80	Slotted	4.5	125	1.02
	Phillips	2	100	Slotted	6.5	150	
		0	==				
	Square	1	100				
	Square	2	125				



2 Piece Insulated SlimLine Slotted & Phillips Screwdrivers Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, Qup to 1000 Volt. Individually Tested to 10,000Volts. High quality CV steel, through hardened. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools.

Item	•	==	‡ (←	
No.	Size	mm	mm	mm	lbs.	
32189	2	100	4.5	125	.37	



Toll Free: (800) 346-8274



SHOP NOW

Wiha Insulated Screwdrivers with SoftFinish® Cushion Grip Handle






☆1000Volt

320 Slotted Screwdriver, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, \diamondsuit up to 1000 Volt. Individually Tested.

Item	‡◆	‡ ()	‡•			===			
No.	mm	Inch	Inch	mm	Inch	mm	Inch	lbs.	pkg.
32005	2.0	.078	5/64	60	3.0	164	6.5	.05	10
32010	2.5	.098	3/32	75	3.0	179	7.1	.06	10
32012	3.0	.118	1/8	100	4.0	204	8.0	.07	10
32015	3.5	.139	9/64	100	4.0	204	8.0	.07	10
32017	4.0	.157	5/32	100	4.0	211	8.3	.12	10
32023	4.5	.177	3/16	100	4.0	211	8.3	.12	10
32024	4.5	.177	3/16	125	5.0	236	9.3	.12	10
32027	4.5	.177	3/16	150	6.0	261	10.2	.14	10
32025	4.5	.177	3/16	175	7.0	286	11.2	.13	10
32028	4.5	.177	3/16	200	8.0	311	12.3	.15	10
32031	5.5	.216	7/32	125	5.0	243	9.5	.15	10
32026	5.5	.216	7/32	175	7.0	293	11.5	.21	10
32034	6.0	.236	15/64	150	6.0	268	10.6	.21	10
32039	6.5	.255	1/4	150	6.0	268	10.6	.21	10
32042	8.0	.315	5/16	175	7.0	299	11.8	.34	10
32045	10.0	.393	3/8	200	8.0	318	12.5	.39	10



32090	4 Piece	4 Piece Slotted & Phillips Set									
Item		40	==	· ¦👄		•	==				
No.		mm	mm	mm		Size	mm	.76 lbs.			
32090	Slotted	3.5	100	0.6	Phillips	1	80				
	Slotted	4.5	125	1.0	Phillips	2	100				



\pm 1000Volt

321 Phillips Screwdriver, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, $\stackrel{\textstyle <}{\sim}$ up to 1000 Volt. Individually Tested. Blade high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item	•			==	===	₽	
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
32100	0	60	2.4	164	6.5	.06	10
32101	1	80	3.0	191	7.5	.12	10
32102	2	100	4.0	218	8.6	.20	10
32103	3	150	6.0	268	10.6	.34	10
32104	4	200	8.0	318	12.5	.39	10



32092	6 Piece Slotted & Phillips Set										
Item		10	=-			•		₽			
No.		mm	mm	mm		Size	mm	lbs.			
32092	Slotted	3.5	100	0.6	Phillips	1	80	1.31			
	Slotted	4.5	125	1.0	Phillips	2	100				
	Slottod	6.5	150	1 2	Dhilling	2	150				


vv	
32091	5 Piece Slotted & Phillips Set
Item	;
Al-	

1

Item		‡() =	- :=		0	::-	₹
No.		mm mi	n mm		Size	mm	lbs.
32091	Slotted	3.0 10	0.6	Phillips	1	80	1.31
	Slotted	4.5 12	5 1.0	Phillips	2	100	
	Slotted	6.5 15	0 1.2				

_

Wiha Insulated Screwdriver Sets



32094	13 Piece Slotted & Phillips Set	
Item No).	<u></u>
32094	Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 5.5, 6.5, 8.0, 10.0mm	lbs.
	Phillips: 0, 1, 2, 3	2.3



32093	10 Piece Slotted & Phillips Set	
Item No).	-
32093	Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 6.5	lbs.
	Phillips: 0, 1, 2, 3	1.63



≙1000Volt

32190	15 Piece Slotted, Phillips & Inch Nut Drivers	Set
Item No		
32190	Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 6.5, 8.0mm	5.9
	Phillips: 1, 2, 3	
	Nut Drivers Inch: 1/4, 5/16, 3/8, 7/16, 1/2"	



32095 19 Piece Slotted, Phillips, Square, Xeno Screwdriver Set
Insulated Screwdriver set in a light weight tool box tray.

Item No.

32095 Slotted: 2.5, 3.0, 3.5, 4.0, 4.5, 5.5, 6.0, 6.5, 8.0, 10.0mm
Phillips: #0, #1, #2, #3

Square: #1, #2
Ibs. Xeno Terminal: #1, #2
4.92 Single Pole Voltage Detector 110V to 250V

SHOP NOW

Wiha Insulated Hex Mertic Screwdrivers



Hex Metric Screwdriver, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, Aup to 1000 Volt. Individually Tested. Blade high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item				===	==	•••	
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
32302	2.5	75	3.0	179	7.0	.06	10
32303	3.0	75	3.0	179	7.0	.08	10
32304	4.0	75	3.0	186	7.3	.12	10
32305	5.0	75	3.0	186	7.3	.15	10
32306	6.0	100	3.9	218	8.6	.24	10
32308	8.0	100	3.9	218	8.6	.34	10



32366	6 Piece Insulated Hex Metric Screw	wdriver Set
Item No	· 32366	↓ lbs.
Hex Me	tric: 2.5, 3.0, 4.0, 5.0, 6.0, 8.0mm	1.06

Wiha Insulated Square Tip Screwdrivers



Square Tip Screwdriver, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E and CSA, ☆ up to 1000 Volt. Individually Tested. Blade high alloy CVM steel, hardened, black finish. Insulation molded directly onto blade.

Item	0	=	=	==	==	←	
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
35811	1	100	4.0	210	8.2	.12	10
35812	2	150	6.0	268	10.5	.19	10



35890	6 Piece Insulated Slotted, Phillips & Square Screwdrivers							
Item No	Item No. 35890							
	Slotted: 4.5 x 125mm, 6.5 x 150mm	lbs.						
	Phillips: 1 x 80mm, 2 x 100mm	.83						
	Square: 1 x 100mm, 2 x 150mm							

35891	6 Piece Insulated Slotted, Phillips & Sc	uare Screwdrivers
Item No	- 35891	↓ ∵ lbs.
Slotted	: 3.0, 5.5mm Phillips: 1, 2 Square: 1, 2	.83

Toll Free: (800) 346-8274

SHOP NOW

Wiha Insulated Nut Drivers



322 Metric Nut Drivers, With Wiha-SoftFinish® Handle Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, $\stackrel{.}{\simeq}$ up to 1000 Volt. Individually

Tested. Blade CVM steel, hardened. Insulation molded directly onto blade. Deep drawn 1" socket. Wiha-SoftFinish® handle, multi-component.

Item	0		==	==	↓	
No.	mm	mm	mm	Inch	lbs.	pkg.
32206	4.0	125	236	9.3	.15	10
32209	5.0	125	236	9.3	.16	10
32212	5.5	125	236	9.3	.16	10
32215	6.0	125	236	9.3	.16	10
32218	7.0	125	243	9.6	.25	10
32221	8.0	125	243	9.6	.25	10
32224	9.0	125	243	9.6	.25	10
32227	10.0	125	243	9.6	.27	10
32230	11.0	125	243	9.6	.37	10
32233	12.0	125	243	9.6	.38	10
32236	13.0	125	243	9.6	.39	10
32238	14.0	125	243	9.6	.39	10
32239	15.0	125	243	9.6	.40	10
32240	16.0	125	243	9.6	.42	10
32241	17.0	125	243	9.6	.44	10

322	Inch Nut	Driver	s, Wit	h Wih	a-SoftI	Finish®	Handle
Item	0	==	==	==	<u></u>		

Item	0	==	==	==	<u></u>	
No.	Inch	Inch	mm	Inch	lbs.	pkg.
32255	5/32	5.0	236	9.3	.15	10
32258	3/16	5.0	236	9.3	.15	10
32261	7/32	5.0	236	9.3	.16	10
32264	1/4	5.0	243	9.5	.24	10
32267	5/16	5.0	243	9.5	.25	10
32268	11/32	5.0	242	9.5	.26	10
32270	3/8	5.0	243	9.5	.26	10
32273	7/16	5.0	243	9.5	.36	10
32276	1/2	5.0	243	9.5	.39	10
32278	9/16	5.0	243	9.5	.39	10
32280	5/8	5.0	243	9.5	.41	10



32296	296 11 Piece Nut Driver Set - Inch Sizes										
Item	0	≕	0	==	<u></u>						
No.	Inch	Inch	Inch	Inch	lbs.						
32296	5/32	5.0	3/8	5.0	3.00						
	3/16	5.0	7/16	5.0							
	7/32	5.0	1/2	5.0							
	1/4	5.0	9/16	5.0							
	5/16	5.0	5/8	5.0							
	11/32	5.0									





☆1000Volt

32291	5 Piece Nut Driver Set - Metric Sizes									
Item	0	≕ -	0	≕	-					
No.	mm	mm	mm	mm	lbs.					
32291	6.0	125	9.0	125	1.36					
	7.0	125	10.0	125						
	8.0	125								



32293	7 Piece Nut Driver Set - Metric Sizes										
Item	0	−	0		-						
No.	mm	mm	mm	mm	lbs.						
32293	5.0	125	8.0	125	2.05						
	5.5	125	10.0	125							
	6.0	125	13.0	125							
	7.0	125									



32292	5 Piece Nut Driver Set - Inch Sizes									
Item	0	≕		==	→					
No.	Inch	Inch	Inch	Inch	lbs.					
32292	7/32	5.0	3/8	5.0	1.52					
	1/4	5.0	1/2	5.0						
	5/16	5.0								



\triangle								
4	4	Λ	n	n	١,	<u>'</u>	14	
/ \			.,	.,	w	"	ıT	

32294	7 Piece Nut Driver Set - Inch Sizes									
Item	0	==	0							
No.	Inch	Inch	Inch	Inch	lbs.					
32294	3/16	5.0	3/8	5.0	2.24					
	7/32	5.0	7/16	5.0						
	1/4	5.0	1/2	5.0						
	5/16	5.0								



Wiha Insulated Inch Nut Driver Set



 \pm 1000Volt

32288	9 Piece Nut Driver Set - Inch Sizes. In roll-up pouch										
Item	0		0	==	-						
No.	Inch	Inch	Inch	Inch	lbs.						
32288	3/16	5.0	7/16	5.0	3.16						
	1/4	5.0	1/2	5.0							
	5/16	5.0	9/16	5.0							
	11/32	5.0	5/8	5.0							
	3/8	5.0									

Insulated Single-Pole Voltage Detector





Insulated Single-Pole Voltage Detector. 110-250 Volts. Insulation According To DIN 57860/6 And DIN VDE 0680-6, GS Tested. Blade CVM steel, hardened, nickel-plated. Insulation molded directly onto blade. Amber LED light. 10,000Volt tested.

Item	‡0	==	===	===		
No.	mm	mm	mm	Inch	lbs.	pkg.
25511	3.0	65	145	5.7	.04	1

Insulated Terminal Block Xeno Screwdrivers





307 Combination Terminal Block Xeno Screwdriver, With Wiha SoftFinish® Handle. Insulation According to ASTM F-1505-01, VDE, 0682/part 201, EN/IEC 60900, NFPA70E & CSA specification. Individually Tested. Blade CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip. For combination Slotted/Phillips head terminal screws.

Item	\oplus		==	==	2,3		
No.	Size	mm	mm	Inch	lbs.	pkg.	
30700	1	80	191	7.5	1.23	10	
30701	2	100	218	8.6	1.23	10	

Wiha Insulated TORX® Screwdrivers



TORX® Screwdriver, With Wiha-SoftFinish® Handle
Insulation According to ASTM F-1505-01, New VDE Specification
0682/part 201 and EN/IEC 60900, NFPA70E and CSA, up to
1000 Volt. Individually Tested. Blade high alloy cvm steel,
hardened, black finish. Insulation molded directly onto blade.

Item	0				==	<u> </u>	_
No.	Size	mm	Inch	mm	Inch	lbs.	pkg.
32505	T5	60	2.4	164	6.5	.06	10
32511	T6	60	2.4	164	6.5	.06	10
32516	T7	60	2.4	164	6.5	.06	10
32521	T8	60	2.4	164	6.5	.06	10
32526	T9	60	2.4	164	6.5	.06	10
32531	T10	60	2.4	164	6.5	.06	10
32536	T15	80	3.0	191	7.5	.12	10
32541	T20	80	3.0	191	7.5	.12	10
32546	T25	80	3.0	198	7.8	.17	10
32551	T27	100	4.0	218	8.6	.20	10
32556	T30	100	4.0	218	8.6	.20	10
32561	T40	150	6.0	274	10.8	.30	10




32590	6 Piece TORX ° Set				
Item	0	==	0	==	
No.	Size	mm	Size	mm	lbs.
32590	T8	60	T15	80	.83
	Т9	60	T20	80	
	T10	60	T25	80	



32592	10 Piece TORX®	Set			
Item	0		0		↓
No.	Size	mm	Size	mm	lbs.
32592	T6	60	T15	80	1.2
	T7	60	T20	80	
	T8	60	T25	80	
	Т9	60	T27	100	
	T10	60	T30	100	

Wiha Insulated "BitFlip" Sets





38017 Insulated BitFlip With Slotted/Phillips/TORX® Bits

Wiha cushion grip handle and insulated shaft. Tested to 10,000 volts.

Set includes the following 1/4"	bits:	
\$ (1) Slotted: 4.5, 6.5mm		
Phillips: 1, 2	lbs.	
♥ TORX® : T10, T15, T20, T25	.45	



38016 Insulated BitFlip With Slotted/Phillips/Square Bits

Wiha cushion grip handle and insulated shaft.	Tested to 10,000 volts.
Set includes the following 1/4" bits:	
\$ (1) Slotted: 4.5, 6.5mm	
Phillips: 0, 1, 2, 3	lbs.
	.45



Insulated BitFlip With Slotted/Phillips Bits

Wiha cushion grip handle and insulated shaft. Tested to 10,000 volts.

wina cushion grip nanule and insulated shall.	rested to 10,000 voits.
Set includes the following 1/4" bits:	₹ **
\$ (1) Slotted: 4.5, 5.5, 6.5, 8.0mm	lbs.
Phillips: 0, 1, 2, 3	.45

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.



Wiha Insulated Belt Pack Pouch Sets

Insulation Test Standards:

Insulation according to EN/IEC 60900, ASTM F-1505-01, New VDE 0682/part 201, DIN 7437, NFPA70E & CSA





☆1000Volt

32875 5 Piece Insulated Pliers/Cutters & SlimLine Screwdrivers In Belt Pack Pouch Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated cushion grip drivers, multi-component. Blade CVM tool steel, hardened.

Item No. Insulated Pliers/Cutters & Screwdrivers

9.0" / 225mm Lineman's Pliers 32875 8.0" / 200mm Long Nose Pliers Insulated SlimLine Screwdrivers:

Slotted: 4.5, 6.5mm • Phillips: 2





↑ 1000Volt

32871 3 Piece Insulated Pliers/Cutters & Multi-Bit Set In Belt Pack Pouch Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated multi-bit screwdriver includes Slotted, Phillips & Square bits.

Item No. Pliers/Cutters & Multi-Bit Set 6.3" / 160mm Diagonal Cutters 32871 8.0" / 200mm Long Nose Pliers

> Set includes Bit Holder and the following bits: Slotted: 4.5, 6.5mm • Phillips: 1, 2 • Square: 1, 2





\triangle 1000Volt

32872 5 Piece Insulated Pliers/Cutters & Screwdrivers In Belt Pack Pouch Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard. Insulated cushion grip drivers, multi-component. Blade CVM tool steel, hardened.

Item No. Insulated Pliers/Cutters & Screwdrivers

6.3" / 160mm Diagonal Cutters 32872 8.0" / 200mm Long Nose Pliers **Insulated Screwdrivers:**

Slotted: 3.0, 4.5mm • Phillips: 2





☆1000Volt

32873 3 Piece Insulated Pliers/Cutters In Belt Pack Pouch

Tools meet EN/IEC, ASTM, VDE, NFPA70E & CSA standards. Pliers chrome finish for long lasting corrosion protection. Soft grip ergo designed handle body, safety slip guard.

Insulated Pliers & Cutters Item No. 6.3" / 160mm Diagonal Cutters 32873

8.0" / 200mm Long Nose Pliers

8.0" / 200mm Combination Pliers ₩ lbs. 2.07





Wiha Insulated Tools-Comfort Grip Handles

All Tools In **Dedicated Positions For Quick Storage** & Easy Location **Tracking**














80 Piece Insulated Master Electrician's Tool Set In Rolling Water Tight Traveling Tool Box - 10,000Volt Tested, 1000Volt Ra

OZOOO OC 1 1000 III.Gailatta III.aatt			
Item# 32800 Set Includes:			
6.3" Long Nose Pliers	6.3" Diagonal Cutters		
8.0" Long Nose Pliers	8.0" High Leverage Cutters		
6.3" Bent Nose Pliers	6.3" Cable Cutters		
6.3" Long Flat Nose Pliers	6.3" Stripping Pliers		
9.0" Combo Pliers/Crimpers	8.0" Adjustable Wrench		
Insulated Socket 1/2"	Insulated Nut Driver 7/32"		
Insulated Socket 9/16"	Insulated Nut Driver 1/4"		
Insulated Socket 5/8"	Insulated Nut Driver 5/16"		
Insulated Socket 11/16"	Insulated Nut Driver 3/8"		
Insulated Socket 3/4"	Insulated Nut Driver 7/16"		
Insulated Socket 13/16"	Insulated Nut Driver 5.0mm		
Insulated Socket 7/8"	Insulated Nut Driver 5.5mm		
Insulated Socket 13mm	Insulated Nut Driver 6.0mm		
Insulated Socket 14mm	Insulated Nut Driver 7.0mm		
Insulated Socket 15mm	Insulated Nut Driver 8.0mm		
Insulated Socket 17mm	Insulated Nut Driver 10.0mm		
Insulated Socket 19mm	Insulated Nut Driver 13.0mm		
Insulated Socket 20mm	Insulated Cable Knife 50mm		
Insulated Socket 22mm	2 Meter Ruler In/MM		
Insulated Ratchet 3/8" Drive	Single Pole Voltage Detector-		
Insulated 4.9" Extension 3/8" Dr.	110V to 250V		

Insulated Slotted 2.5mm	Insulated Phillips #0
Insulated Slotted 3.0mm	Insulated Phillips #1
Insulated Slotted 3.5mm	Insulated Phillips #2
Insulated Slotted 4.0mm	Insulated Phillips #3
Insulated Slotted 4.5mm	Insulated Slt/Ph Terminal #1
Insulated Slotted 5.5mm	Insulated Slt/Ph Terminal #2
Insulated Slotted 6.0mm	Insulated Square #1
Insulated Slotted 6.5mm	Insulated Square #2
Insulated Slotted 8.0mm	Insulated Torx T6
Insulated Slotted 10.0mm	Insulated Torx T7
Insulated T-handle Hex 5/32"	Insulated Torx T8
Insulated T-handle Hex 3/16"	Insulated Torx T9
Insulated T-handle Hex 7/32"	Insulated Torx T10
Insulated T-handle Hex 1/4"	Insulated Torx T15
Insulated T-handle Hex 5/16"	Insulated Torx T20
Insulated T-handle Hex 3/8"	Insulated Torx T25
Insulated T-handle Hex 4.0mm	Insulated Torx T30
Insulated T-handle Hex 5.0mm	Insulated L-key 10mm
Insulated T-handle Hex 6.0mm	Insulated L-key 1/2"
Insulated T-handle Hex 8.0mm	

Use & Care Guide For Insulated Tools:


Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70° C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.



Wiha 1000Volt Insulated Tool Sets - Comfort Grip Handles



32877 80 Piece Insulated Mast	ter Flectrician's Set		
Item# 32877 Set Includes:	± lbs. 27.0		
6.3" Long Nose Pliers	6.3" Diagonal Cutters		
6.3" Bent Nose Pliers	8.0" High Leverage Cutters		
8.0" Long Nose Pliers	8.0" Cable Cutters		
6.3" Long Flat Nose Pliers	6.3" Stripping Pliers		
9.0" Combo Pliers/Crimpers	8.0" Adjustable Wrench		
Insulated Slotted 2.0mm	Insulated Nut Driver 7/32"		
Insulated Slotted 2.5mm	Insulated Nut Driver 1/4"		
Insulated Slotted 3.0mm	Insulated Nut Driver 5/16"		
Insulated Slotted 3.5mm	Insulated Nut Driver 3/8"		
Insulated Slotted 4.0mm	Insulated Nut Driver 7/16"		
Insulated Slotted 4.5mm	Insulated Nut Driver 5.0mm		
Insulated Slotted 5.5mm	Insulated Nut Driver 5.5mm		
Insulated Slotted 6.0mm	Insulated Nut Driver 6.0mm		
Insulated Slotted 6.5mm	Insulated Nut Driver 7.0mm		
Insulated Slotted 8.0mm	Insulated Nut Driver 8.0mm		
Insulated Slotted 10.0mm	Insulated Nut Driver 10.0mm		
Insulated Phillips #0	Insulated Nut Driver 13.0mm		
Insulated Phillips #1	Insulated T-handle Hex 5/32"		
Insulated Phillips #2	Insulated T-handle Hex 3/16"		
Insulated Phillips #3	Insulated T-handle Hex 7/32"		
Insulated Slt/Ph Terminal #1	Insulated T-handle Hex 1/4"		
Insulated Slt/Ph Terminal #2	Insulated T-handle Hex 5/16"		
Insulated Torx T6	Insulated T-handle Hex 3/8"		
Insulated Torx T7	Insulated T-handle Hex 4.0mm		
Insulated Torx T8	Insulated T-handle Hex 5.0mm		
Insulated Torx T9	Insulated T-handle Hex 6.0mm		
Insulated Torx T10	Insulated T-handle Hex 8.0mm		
Insulated Torx T15	Insulated L-key 10mm		
Insulated Torx T20	Insulated L-key 1/2"		
Insulated Torx T25	Insulated Cable Knife 50mm		
Insulated Torx T30	2 Meter Ruler In/MM		
Insulated Square #1	Insulated Ratchet 3/8" Dr.		
Insulated Square #2	Insulated 4.9" Extension		
Insulated Socket 1/2"	Insulated Socket 13mm		
Insulated Socket 9/16"	Insulated Socket 14mm		
Insulated Socket 5/8"	Insulated Socket 15mm		
Insulated Socket 11/16"	Insulated Socket 17mm		
Insulated Socket 3/4"	Insulated Socket 19mm		
Insulated Socket 13/16"	Insulated Socket 20mm		
Insulated Socket 7/8"	Insulated Socket 22mm		



32876 66 Pc. Master Electrician's Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, \bigcirc up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished.

Item# 32876	Set Includes:	- lbs. 21.5
8.0" Long Nose		6.3" Side Cutters
6.3" Long Flat Nose		8.0" High Leverage Cutters
9.0" Combo Pliers/Crimpers		6.3" Stripping Pliers
8.0" Cable Cutters		8.0" Adjustable Wrench
Insulated Nut Driver 1/4"		Insulated Slotted 2.0mm
Insulated Nut Di	iver 5/16"	Insulated Slotted 2.5mm
Insulated Nut Dr	iver 11/32"	Insulated Slotted 3.0mm
Insulated Nut Dr	iver 3/8"	Insulated Slotted 4.0mm
Insulated Nut Dr	iver 7/16"	Insulated Slotted 4.5mm
Insulated T-hand	dle Hex 4.0mm	Insulated Slotted 5.5mm
Insulated T-hand	dle Hex 5.0mm	Insulated Slotted 6.0mm
Insulated T-hand	dle Hex 6.0mm	Insulated Slotted 8.0mm
Insulated T-hand	dle Hex 8.0mm	Insulated Slotted 10.0mm
Insulated T-hand	dle Hex 5/32"	Insulated Phillips #0
Insulated T-hand	dle Hex 3/16"	Insulated Phillips #1
Insulated T-hand	dle Hex 7/32"	Insulated Phillips #2
Insulated T-handle Hex 1/4"		Insulated Phillips #3
Insulated T-hand	dle Hex 5/16"	Insulated Torx T8
Insulated T-handle Hex 3/8"		Insulated Torx T10
Insulated Hex L-key 10.0mm		Insulated Torx T15
Insulated Hex L-	-key 1/2"	Insulated Torx T20
Insulated Socke	t 1/2"	Insulated Torx T25
Insulated Socke	t 9/16"	Insulated Torx T30
Insulated Socke	t 5/8"	Insulated Square #1
Insulated Socke	t 11/16"	Insulated Square #2
Insulated Socke	t 3/4"	Insulated Slt/Ph Terminal #1x80
Insulated Socke	t 13/16"	Insulated Slt/Ph Terminal #2x100
Insulated Socke	t 7/8"	Insulated Cable Knife 50mm
Insulated Socke	t 8.0mm	Insulated Extension 4.9"
Insulated Socke	t 10.0mm	Insulated Ratchet 3/8" Driver
Insulated Socke	t 13.0mm	Insulated Socket 17.0mm
Insulated Socke	t 14.0mm	Insulated Socket 19.0mm
Insulated Socke	t 15.0mm	Insulated Socket 22.0mm

Wiha 1000Volt Insulated Tool Sets - Comfort Grip Handles



☆1000Volt

48 Pc. BIG SET

48 Piece Insulated Tool Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, aux to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. Cushion Grip Insulated handles. Canvas tool bag.

Item# 32874	Set Includes:	- → lbs. 19.4
6.3" Long Nose Pliers		6.3" Side Cutters
8.0" Long Nose Pliers		8.0" High Leverage Cutters
6.3" Combination Pliers		6.3" Stripping Pliers
9.0" Combo Pliers/Crimpers		8.0" Adjustable Wrench
Slotted: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.5, 6.0, 6.5, 8.0mm		

Phillips: #0, 1, 2, 3 Square: #1, 2 Slt/Ph Terminal: #1, 2 TORX: T8, T9, T10, T15, T20, T25, T27, T30 Hex Inch: 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"

Nut Driver Inch: 7/32, 1/4, 5/16, 3/8, 7/16, 1/2"

Insulated Cable Knife & 2 Meter In/MM




32878 13 Piece Pliers & Screwdriver Set. In Tool Box		
Item#32878 Set Includes: July lbs. 6.60		
8.0" Long Nose	9.0" Combo Pliers/Crimpers	
8.0" High Leverage Cutters	50mm Cable Stripping Knife	
Insulated Slotted: 3.0mm	Insulated Phillips: #1	
Insulated Slotted: 4.5mm	Insulated Phillips: #2	
Insulated Slotted: 6.0mm	Insulated Square: #1	
Insulated Slt/Ph Terminal: #1	Insulated Square: #2	
Insulated Slt/Ph Terminal: #2		



32879 25 Piece Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. In tool box.

Item# 32879 Set Includes:	↓ ↓ lbs. 11.92	
8.0" Long Nose	6.3" Stripping Pliers	
9.0" Combination Pliers	Inch & Metric Folding Ruler	
8.0" High Leverage Cutters	8.5" Insulated Knife	
Slotted: 3.0, 4.5, 6.0mm	Phillips: #1, #2	
Square: #1, #2	Terminal Block Driver: #1, #2	
Inch Nut Driver: 1/4, 5/16, 11/32, 3/8, 7/16, 1/2"		
Metric Nut Driver: 7.0, 8.0, 10.0, 13.0mm		



32896 31 Piece Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, \triangle up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome/nickel plated, mirror-polished. Set includes 6ft. Fiber glass folding ruler.

plates, illinoi penenesi eet illetaee etti illet glaee letailig talet.		
Item# 32896 Set Includes:	↓ → lbs. 12.85	
6.3" Long Nose Pliers	6.3" Side Cutters	
8.0" Long Nose Pliers	8.0" High Leverage Cutters	
7.0" Linemans Pliers	6.3" Stripping Pliers	
9.0" Combination Pliers	6.3" Round Nose Pliers	
Slotted: 2.0, 2.5, 3.0, 3.5, 4.5, 5.5, 6.5, 8.0, 10.0mm		
Phillips: #0, #1, #2, #3		
Inch Nut Driver: 5/32, 3/16, 7/32, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16"		



Wiha Insulated Pliers with High Visibility Comfort Grip Handle

← 1000Volt



- Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.
- In zipper carry case

V



eq 1000Volt

10 Piece Pliers & Screwdriver Set
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM
F-1505-01, NFPA70E & CSA, ☆ up to 1000 volt. Individually Tested.

	· · · · · · · · · · · · · · · · · · ·			
Item# 32891	Set Includes:	↓ → lbs. 5.54		
8.0" Combinati	on Pliers	8.0" Long Nose		
8.0" Side Cutte	ers	8.0" Cable Cutters		
6.3" Universal	Wire Stripper			
Insulated Philli	ps #1	Insulated Slotted 4	.5mm	
Insulated Philli	ps #2	Insulated Slotted 6	.5mm	
Insulated Philli	ps #3			



- Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.
- In zipper carry case


↑ 1000Volt


32895 14 Piece Pliers & Screwdriver Set

Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, $\stackrel{\frown}{\sim}$ up to 1000 volt. Individually Tested.

T-1303-01, NEFATUE & CSA,	Tup to 1000 voit. Individually les	ıeı
Item# 32895 Set Includes: €	→ lbs. 6.60	
8.0" Long Nose	6.3" Side Cutters	
9.0" Combination Pliers	8.0" High Leverage Cutters	
6.3" Stripping Pliers	Insulated Slotted 2.5mm	
Insulated Phillips #1	Insulated Slotted 3.0mm	
Insulated Phillips #2	Insulated Slotted 3.5mm	
Insulated Phillips #3	Insulated Slotted 4.5mm	
Insulated Slotted 2.0mm	Insulated Slotted 6.5mm	








10 Piece Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, $\stackrel{\frown}{\sim}$ up to 1000 volt. Individually Tested. Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished. In molded tool box

Item#32892 Set Includes:	↓ • Ibs. 6.64
8.0" Bent Nose	8.0" Combination Pliers
6.3" Long Nose	6.3" Side Cutters
Insulated Phillips #0	Insulated Slotted 3.0mm
Insulated Phillips #1	Insulated Slotted 4.5mm
Insulated Phillips #2	Insulated Slotted 6.5mm





☆ 1000Volt

32894 12 Piece Pliers & Scre	wdriver Set In Molded Tool Box
Item# 32894 Set Includes: ₩	→ lbs. 8.60
8.0" Bent Nose	8.0" Combination Pliers
6.3" Long Nose	6.3" Side Cutters
Insulated Slotted 4.5mm	Insulated Nut Driver 1/4"
Insulated Slotted 6.5mm	Insulated Nut Driver 5/16"
Insulated Phillips #1	Insulated Nut Driver 3/8"
Insulated Phillips #2	Insulated Nut Driver 1/2"

wiha

SHOP NOW

Wiha Insulated Pliers with High Visibility Comfort Grip Handle

 Pliers drop-forged from special tool steel, individually high frequency induction hardened, chrome and nickel plated, mirror-polished.



\uparrow 1000Volt

32889 8 Piece Pliers & Cutters Set

Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, \Leftrightarrow up to 1000 volt. Individually Tested.

T 1000 01, 1411 A702 a COA, ap to 1000 voit. maividually rest	
Item#32889 Set Includes:	↓ ⁺ lbs. 4.63
6.3" Long Nose Pliers	8.0" Long Nose Pliers
6.3" Lineman's Pliers	6.3" Diagonal Cutters
9.0" Lineman's Pliers	8.0" High Lev. Cutters
6.3" Wire Stripping Pliers	Electrician's Knife





\uparrow 1000Volt

32869 14 Piece Pliers/Cutters & Screwdrivers Set
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM
F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested.

item# 32869 Set includes:	₩ IDS. 6.52
9.0" Lineman's Pliers	8.0" High Leverage Cutters
8.0" Cable Cutters	8.0" Long Nose Pliers
6.0" Stripping Pliers 10-20 AWG	
SlimLine Slotted 3.0mm	SlimLine Phillips #1
SlimLine Slotted 4.5mm	SlimLine Phillips #2
SlimLine Slotted 6.5mm	SlimLine Terminal #2
SlimLine Square #1	Single Pole Tester
SlimLine Square #2	





☆ 1000Volt

32867 10 Piece Pliers & S	Screwdriver Set In Canvas Pouch
Item#32867 Set Includes:	↓ Ibs. 4.06
6.3" Diagonal Cutters	9.0" Combo Pliers
6.3" Long Nose Pliers	6.3" Wire Strippers
7.0" Crimping Pliers	
Insulated Slotted 4.5mm	Insulated Phillips #1
Insulated Slotted 6.0mm	Insulated Phillips #2
Insulated Square: #2	





\uparrow 1000Volt

32868 10 Piece Pliers & Screwdriver Set In Canvas Pouch								
Item#32868 Set Includes:	↓ • lbs. 4.24							
7.0" Diagonal Cutters	9.0" Combo Pliers							
8.0" Long Nose Pliers	6.3" Wire Strippers							
7.0" Crimping Pliers								
Insulated Slotted 3.0mm	Insulated Phillips #1							
Insulated Slotted 4.5mm	Insulated Phillips #2							
Insulated Slotted 6.0mm								


WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.

Use & Care Guide For Insulated Tools:

Store tools to minimize risk of damage to insulation, always wear approved eye protection, Inspect insulation prior to each use of any insulated tool. Use insulated tools where the ambient temperature is between -20 to +70 $^{\circ}$ C. Have a qualified safety technician visually inspect insulation on tools annually for safe use.





Insulated Linemans Pliers With Crimpers

5-In-1 Lineman's Pliers



With Lower Crimping Jaw

Insulated High Leverage Combination Pliers

Lineman's



Insulated Combination Lineman's Pliers



Insulated Lineman's Pliers "5-In-1" Professional Design Insulation According to EN/IEC, ASTM, NFPA70E & CSA,

☆ up to 1000 volt. Individually Tested.

Deep cut radius conduit jaws for non-slip handling. Sure grip knurled & cross hatched flat jaw for non-slip griping. Extra long induction hardened precision matched cutting edges. Lower crimping jaw accepts most standard non-insulated electrical connectors. Large head with square anvil surface on each side. Made from premium CV tool steel forgings. Two component cushion grips for best user comfort.

Item	→	\rightarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32821	225	9.0	#4	1	.88

Extra long cutting edge for flat and round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 64HRC. C 60 Special tool steel. Use for gripping, pulling & holding as well as cutting wires and cables ranging in hardness from soft to extremely hard. Two component soft grip ergonomic handles.

Item	→	→	Cutting Capacity		←
No.	mm	Inch	Copper AWG	Pkg.	wt.
32820	225	9.0	#4	1	.86

201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, Qup to 1000 volt. Individually Tested. DIN ISO 5746 Extra long cutting edge for flat & round cables. Serrated jaws. Cutting edges additionally induction hardened to approx. 60HRC. Special CV tool steel forgings, Chrome finish. Use for gripping and holding as well as cutting soft and hard wires and cables. Two component soft grip ergonomic handles.

Item	\leftarrow	\longrightarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32814	160	6.3	#10	1	.53
32816	180	7.0	#9	1	.58
32818	200	8.0	#8	1	.72

Toll Free: (800) 346-8274

wiha


SHOP NOW

Insulated Diagonal Cutters



Insulated High Leverage Diagonal Cutters








Insulated Electrician's Diagonal Cutters



Insulated Serrated Edge Cable Cutters



Insulated Crimping Pliers



Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60 HRC. Special tool steel hardened and tempered. For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item	→ →	Cutting Capacity		•••
No.	mm In	ich Copper AWG	Pkg.	wt.
32830	140 5.	.5 #6	1	.47
32832	160 6.	.3 #6	1	.49
32834	180 7.	.0 #6	1	.62

High Leverage Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. DIN ISO 5749

Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64 HRC.

C 60 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	\leftarrow	\leftrightarrow	Cutting Capacity		-
No.	mm	Inch	Copper AWG	Pkg.	wt.
32835	160	6.3	#6	1	.64
32836	180	7.0	#5	1	.67
32838	200	8.0	#4	1	.80

32861 Diagonal Cutters W/Stripping Holes. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,

up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chrome-nickel plated, mirror-polished. Ergo comfort grip with slip guard. Holes in the cutting edge for stripping copper wire of Ø 1.5 and 2.5.

Item	\leftarrow	\leftarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32861	160	6.3	#6	1	.55

328 Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, wp to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 62 HRC. Special tool steel, hardened & tempered. For cutting of copper & aluminum cables without crushing.

Item	\leftarrow	\leftarrow				₹
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
32826	160	6.3	16	50	1	.42
32828	200	8.0	20	60	1	.67

32841 Insulated Crimping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, $\stackrel{\wedge}{\sim}$ up to 1000 Volt. Individually Tested.

Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 64 HRC. CV 60 special tool steel hardened & tempered.

Item	\leftarrow	\leftarrow				
No.	mm	Inch	mm2	AWG	Pkg.	wt.
32841	180	7.0	0.25-2.5	6-30	1	.57



Insulated Long Nose Pliers



Long Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chromenickel plated, mirror-polished, ergonomic comfort grip with slip guard, half-round jaws, serrated gripping surface.

Item	→	\leftarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32806	160	6.3	#10	1	.32
32808	200	8.0	#8	1	.42

Insulated Bent Nose Pliers



Bent Nose Pliers With Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, $\stackrel{\frown}{\sim}$ up to 1000 volt. Individually Tested.

Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chrome-nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Half-round jaws, serrated gripping surface, nose bent 40°.

Item	\leftarrow	\leftarrow	Cutting Capacity		↓
No.	mm	Inch	Copper AWG	Pkg.	wt.
32804	200	8.0	#8	1	.43
32807	160	6.3	#10	1	.32

Round Nose Pliers



32870 Round Nose Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. Drop-forged from special tool steel, individually induction hardened, chrome and nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Serrated jaws.

Item	←→	←→		←
No.	mm	Inch	Pkg.	wt.
32870	160	6.3	1	.34

Insulated Long Flat Nose Pliers



32810 Long Flat Nose Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. DIN ISO 5745

Extra long head. Serrated Jaws are induction hardened. Special CV tool steel forgings, Chrome finish. Two component Soft Grip handles. Use for Gripping and right-angle bending of wires and sheet metal parts.

Item	→→	→→	_	, , ,
No.	mm	Inch	Pkg.	wt.
32810	160	6.3	1	.39

Wiha Canvas Pliers Holster

- · Canvas holster with belt clip and belt loop
- · Security pliers strap
- · Screwdriver holder in the front

91256	Pliers Canvas Holster							
Item	Widt	h	Heigh	t 🕶				
No.	Size		Size	lbs.	pkg.			
91256	3.5	Х	6.75	.15	1			





Toll Free: (800) 346-8274



SHOP NOW

Insulated Stripping Pliers



32860 Stripping Pliers. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA,

☆ up to 1000 volt. Individually Tested. Heavy duty forged with induction hardened cutting edges for even stripping of insulation.

Drop-forged from special tool steel, chrome and nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Spring and adjusting screw, for stripping up to Ø 5mm/#4 Awg.

Item	\leftrightarrow	\rightarrow	Stripping Capacity		<u></u>
No.	mm	Inch	Copper AWG	Pkg.	wt.
32860	160	6.3	#4 - #28	1	.50



10250 Insulated Stripping Pliers. Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification.

Individually Tested. Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm, AWG 20 / 18 / 16 / 14 / 12 / 10.

Item No.	mm	Inch	Ø	AWG	Pkg.	lbs.
10250	160	6.3"	0.81-2.59	20-10	5	.26

Switch Cabinet Key



21103 Switch Cabinet Keys

For applications with all common switch cabinets and locking systems. Diecast Zinc

Item No.	mm	Inch	Pkg.	lbs.
21103	76	3.0"	5	.22

Tools Meet 10,000 Volt Test Standards Rated to 1000Volt ac or 1500 Volt dc


91230	Inomic Canvas Holster						
Item	Widt	h	Height	•			
No.	Size		Size	lbs.	pkg.		
91230	4.0	Х	4.5	.05	1		



SHOP NOW

Premium Tool

Wiha Inomic 1000Volt Insulated Pliers



Tools Meet 10,000 Volt Test Standards Rated to 1000 Volt ac or 1500 Volt dc

Inomic Combo Pliers. Insulation According to EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, Qup to 1000 volt. Individually Tested. DIN ISO 5749 Precision machined forged head. Induction hardened for longest tool life. Cross hatched flat jaw & deep cut radius jaws for secure gripping of the work piece. Cutting edges are matched for precise cutting action. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue. Palm side of grip has molded soft panel for added comfort in prolonged use.

Item		→	\leftarrow	Cutting Capacity					
No.		mm	Inch	Copper AWG	Pkg.	lbs.			
32850		180	7.0	#6	1	.46			
32852	Inomic Long	Nose	Pliers						
Item		→	\leftrightarrow	Cutting Capacity					
No.		mm	Inch	Copper AWG	Pkg.	lbs.			
32852		160	6.3	#6	1	.43			
32854	32854 Inomic Diagonal Cutters								
Item		→	\leftarrow	Cutting Capacity		•••			
No.		mm	Inch	Copper AWG	Pkg.	lbs.			
32854		160	6.3	#6	1	.41			

Insulation Standards:

EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA

☆1000Volt

32859 3 Pc. Insulated Inomic Pliers/Cutters Set Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue.

Item# 32859 Set Includes:	
32850 - Combo Pliers	32854 - Diagonal Cutters
32852 - Long Nose Pliers	91230 - Inomic Holster (Includes 3)







Insulated Lineman's Pliers With Crimpers



Insulated Industrial Lineman's Pliers "5-In-1" Professional Design Insulation According to EN/IEC, ASTM, NFPA70E & CSA, up to 1000 volt. Individually Tested. Deep cut radius conduit jaws for non-slip handling. Sure grip knurled & cross hatched flat jaw for non-slip griping. Extra long induction hardened precision matched cutting edges. Lower crimping jaw accepts most standard non-insulated electrical connectors. Large head with square anvil surface on each side. Premium CV tool steel forgings.

Item	→	\leftarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32917	225	9.0	#4	1	.98

Insulated Long Nose Pliers With Cutters



Insulated Industrial Long Nose Pliers With Cutters.
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM
F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested.
Drop-forged from special tool steel, cutters additionally induction
hardened (approx. 60 HRC), half-round jaws, serrated gripping surface.
Industrial brushed finish. Ergonomic comfort grip with slip guard.

Item	+	\rightarrow	Cutting Capacity		₽
No.	mm	Inch	Copper AWG	Pkg.	wt.
32926	160	6.3	#10	1	.36
32923	200	8.0	#8	1	.46

Long life high performance dynamic 60/40 joint 1000volt

Insulated Industrial Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60 HRC. Special tool steel hardened and tempered. Industrial brushed finish. For soft, medium hard wire & piano wire.

Item	\longleftrightarrow	Cutting Capacity		←
No.	mm Inch	Copper AWG	Pkg.	wt.
32933	160 6.3	#6	1	.64
32929	200 8.0	#6	1	.80





Insulated Industrial Stripping Pliers. Insulation According to VDE 0682/part 201, DIN 7437, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, 1000 volt rated. Individually Tested.

DIN ISO 5745 Made from Premium CV tool steel forgings. Induction hardened jaws and cutters to 60 HRC. Industrial brushed finish. Two component ergo cushion grips for best user comfort. Spring & adjusting screw, for stripping up to Ø 5mm/#4 Awg.

Item	\leftrightarrow	→	Stripping Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
32947	160	6.3	#4 - #28	1	.46

Insulated Combo Pliers With Dynamic Joint



Insulated Industrial High Leverage Combination Pliers.
Insulation According to EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA, up to 1000 volt. Individually Tested. DIN ISO 5746

Extra long cutting edge for flat and round cables. Serrated jaws.
Cutting edges additionally induction hardened to approx. 60HRC.
Use for gripping, pulling & holding as well as cutting wires and cables ranging in hardness from soft to extremely hard. Industrial brushed finish. Two component soft grip ergonomic handles.

Item	→→	\leftarrow	Cutting Capacity		←
No.	mm	Inch	Copper AWG	Pkg.	wt.
32930	200	8.0	#4	1	.92

Insulated Heavy Duty Cable Cutters



Insulated Industrial Serrated Edge Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E and CSA, up to 1000 Volt. Individually Tested. Light, clean cutting ground precision cutting edges. Durable cutting is achieved through additional inductive hardening to approx. 60 HRC. Premium CV tool steel forgings. For cutting of copper & aluminum cables without crushing. Two component ergo cushion grips for best user comfort.

Item	→	→				
No.	mm	Inch	Ø	mm2	Pkg.	lbs.
32927	200	8.0	20	60	1	.78

Insulated Crimpers Industrial electric 1000volt

Insulated Industrial Crimping Pliers. Insulation
According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01,
NFPA70E and CSA, up to 1000 Volt. Individually Tested.
Semi-circular profiles for secure connection between end sleeve and conductor. Long life is achieved through additional induction hardening to 60 HRC. Industrial brushed finish. Two component ergo cushion grips for best user comfort. Crimps 6 - 30 AWG Connectors.

Item	→	\leftarrow				-,-
No.	mm	Inch	mm2	AWG	Pkg.	wt.
32945	180	7.0	0.25-2.5	6-30	1	.64



Wiha Insulated Industrial Tool Sets





In Belt Pack Pouch


> Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards



32985 7 Pc. Insulated Industrial Pliers/Cutters & Screwdrivers

Item No. Insulated Pliers/Cutters & Screwdrivers

32985 8.0" Combo Pliers, 6.3" Long Nose, 6.3" Diagonal Cutters Insulated Drivers: Slotted: 3.0, 4.5mm • Phillips: #1, #2



32999 9 Piece Insulated Industrial Pliers & Cutters Set

Insulated pliers & cutters set in a light weight tool box tray.

Mana Na

item No.		
32999	9.0" Lineman's Pliers	8.0" High Leverage Combo Pliers
	6.3" Long Nose Pliers	8.0" Cable Cutters
↓	8.0" Long Nose Pliers	6.3" Stripping Pliers
lbs.	6.3" Diagonal Cutters	7.0" Crimping Pliers
6.34	8.0" Diagonal Cutters	

Wiha Insulated Tool Tray Sets





Tools meet ASTM, IEC, VDE, EN. NFPA & CSA standards

Individually Tested

32981 3 Pc. Insulated Industrial Pliers & Cutters

Insulated Pliers & Cutters

32981 8.0" Combo Pliers, 8.0" Long Pliers, 8.0" Diagonal Cutters



Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards

Individually Tested

← 1000Volt

32983 5 Pc. Insulated Industrial Diagonal Cutters & Screwdrivers

Insulated Diagonal Cutters & Screwdrivers

32983 6.3"/160mm Diagonal Cutter

Insulated Drivers: Slotted: 3.0, 4.5mm • Phillips: #1, #2



Tools meet ASTM, IEC, VDE, EN, NFPA & CSA standards

Individually Tested

eq 1000Volt

6 Pc. Insulated Industrial Combo Pliers & Screwdrivers 32984

Insulated Combination Pliers & Screwdrivers 32984 8.0" Combination Pliers & 8" Long Nose Pliers

Drivers: Slotted: 3.0, 4.5mm • Phillips: #2 • Square: #2

lbs. 2.06

28 Piece Insulated Industrial Pliers & Cutters Set

Insulated pliers & cutters set in a light weight tool box tray.

	o o	•		
Item No.	Set Includes:	-		
32989	9.0" Lineman's Pliers	lbs.		
	8.0" High Leverage Combo Pliers	6.34		
	6.3" & 8.0" Long Nose Pliers			
	8.0" Cable Cutters			
	6.3" & 8.0" Diagonal Cutters			
	6.3" Stripping Pliers			
	7.0" Crimping Pliers			
	Slotted: 2.5, 3.0, 3.5, 4.0, 4.5, 5.5, 6.0,	6.5, 8.0, 10.0mm		
	Phillips: #0, #1, #2, #3			
	Xeno Slotted/Phillips: #1, #2 & Square:	#1, #2		

Voltage Detector 3.0mm 110-225Volts

wiha

SHOP NOW

Wiha Insulated Industrial Tool Sets

In Roll Out Pouch



 \pm 1000Volt

0

32986 11 Pc. Pliers & Screwdriver Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505-01, NFPA70E,

→ up to 1000 volt. Individually Tested. In Roll Out Pouch

Item# 32986Set Includes:Item Item6.3" Long Nose Pliers6.3" Diagonal Cutters8.0" Combination Pliers6.3" Stripping Pliers

Insulated Slotted: 3.0, 4.5, 5.5mm

Insulated Phillips: #1, #2 Insulated Square: #1, #2

In Roll Out Pouch



1000Volt

Item# 32987 Set Includes:
6.3" Long Nose Pliers
6.3" Diagonal Cutters
8.0" Long Nose Pliers
8.0" Lineman's w/Cutters
8.0" Cable Cutters
7.0" Crimpers





22 Pc. Pliers & Cutters Set. Insulation According to VDE 0682/part 201, DIN EN 60900, EN/IEC 60900, ASTM F-1505-01, NFPA70E,

→ up to 1000 volt. Individually Tested. In Roll Out Pouches

Item#32988Set Includes:↓ → Ibs. 5.748.0" Long Nose Pliers6.3" Diagonal Cutters9.0" Lineman's w/Cutters8.0" H.D. Diagonal Cutters8.0" Cable Cutters6.3" Stripping Pliers

7.0" Crimping Pliers

15 Pc. SlimLine Blade Set includes: Insulated SlimLine Blade Holder

Slotted: 3.0, 4.0, 5.5, 6.5 Phillips: #1, #2 Xeno: #1, #2

TORX*: T8, T10, T15, T20 Square: #1, #2



Now in canvas tool bag

≙1000Volt

32390 11 Pc. Pliers & Driver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,

weight the weight to the weig

8.0" Linemans Pliers 6.3" Long Nose Pliers W/Cutter

8.0" Long Nose Pliers W/Cutter 6.3" Diagonal Cutter

8.0" High Leverage Cutter

Insulated Phillips #0 Insulated Slotted 3.0mm(1/8")
Insulated Phillips #1 Insulated Slotted 4.5mm(3/16")
Insulated Phillips #2 Insulated Slotted 6.5mm(1/4")



32973 22 Pc. Pliers & Driver Set. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E & CSA,

A up to 1000 volt. Individually Tested. In molded tool box Set Includes:

→ lbs. 8.70 Item# 32973 9.0" Linemans Pliers W/Cutters 8.0" Long Nose Pliers W/Cutter 50mm Cable Stripping Knife 8.0" Diagonal Cutters Insulated Slim Phillips #1 Insulated Slim Slotted 3.5mm(9/64") Insulated Slim Phillips #2 Insulated Slim Slotted 4.5mm(3/16") Insulated Slim Xeno #1 Insulated Slim Square #1 Insulated Slim Xeno #2 Insulated Slim Square #2 Insulated T-handle Hex Inch: 5/32, 3/16, 7/32, 1/4, 5/16, 3/8" Insulated Inch Nut Drivers: 3/8, 7/16, 1/4, 5/16"

WARNING!

Insulated Tools are intended to provide protection against accidental contact with charged energized circuits. For maximum safety we recommend de-energizing all circuits whenever possible before starting work on electrical apparatus or conductors. Always visually inspect insulation on tools before use, do not use tools if insulation shows signs of wear or damage to the insulated areas of the tool. Wear appropriate eye protection when using hand tools. Use NFPA70E certified insulated protective outer wear when appropriate.



Numerical Index by Item Number

| Item No. Page |
|---------------|---------------|---------------|---------------|---------------|
| 10250 37 | 20012 5 | 21044 7 | 28724 18 | 31439 12 |
| 11625 15 | 20013 5 | 21046 7 | 28726 18 | 31491 12 |
| 11630 15 | 20014 5 | 21048 7 | 28727 18 | 31493 12 |
| 11950 15 | 20015 5 | 21050 7 | 28734 18 | 31495 13 |
| 11960 16 | 20016 5 | 21052 7 | 28736 18 | 31496 13 |
| 11975 16 | 20017 5 | 21054 7 | 28737 18 | 31506 12 |
| 12326 14 | 20018 5 | 21056 7 | 28791 18 | 31507 12 |
| 12327 13 | 20019 5 | 21057 7 | 28792 18 | 31508 12 |
| 12851 10 | 20020 5 | 21058 7 | 29006 11 | 31509 12 |
| 12852 13 | 20022 5 | 21060 7 | 29009 13 | 31510 12 |
| 12853 15 | 20024 5 | 21062 7 | 29012 15 | 31511 12 |
| 12854 11 | 20027 5 | 21064 7 | 29240 15 | 31512 12 |
| 12855 11 | 20030 5 | 21066 7 | 29250 15 | 31513 12 |
| 12856 13 | 20032 5 | 21068 7 | 30700 26 | 31514 12 |
| 12857 13 | 20091 4 | 21093 7 | 30701 26 | 31515 12 |
| 12858 15 | 20093 4 | 21094 7 | 30746 21 | 31516 12 |
| 12859 15 | 20131 5 | 21095 7 | 30747 21 | 31517 12 |
| 13650 9 | 20133 5 | 21096 7 | 31326 10 | 31518 12 |
| 13651 9 | 20135 5 | 21103 37 | 31327 10 | 31519 12 |
| 13652 9 | 20136 5 | 21208 6 | 31328 10 | 31520 12 |
| 13653 9 | 20137 5 | 21210 6 | 31329 10 | 31521 12 |
| 13654 9 | 20138 5 | 21212 6 | 31330 10 | 31522 12 |
| 13655 9 | 20140 5 | 21213 6 | 31331 10 | 31524 12 |
| 13656 9 | 20141 5 | 21214 6 | 31332 10 | 31590 12 |
| 13657 9 | 20142 5 | 21217 6 | 31333 10 | 31592 13 |
| 13658 9 | 20144 5 | 21219 6 | 31334 10 | 31595 13 |
| 13659 9 | 20145 5 | 21290 6 | 31335 10 | 31608 14 |
| 13662 9 | 20146 5 | 21325 6 | 31336 10 | 31609 14 |
| 13663 9 | 20147 5 | 21327 6 | 31337 10 | 31610 14 |
| 13664 9 | 20148 5 | 21329 6 | 31338 10 | 31611 14 |
| 13665 9 | 20149 5 | 21331 6 | 31339 10 | 31612 14 |
| 13666 9 | 20190 4 | 21333 6 | 31340 10 | 31613 14 |
| 13667 9 | 20192 4 | 21335 6 | 31341 10 | 31614 14 |
| 13668 9 | 20194 5 | 21391 6 | 31342 10 | 31615 14 |
| 13669 9 | 20196 5 | 25511 26 | 31343 10 | 31616 14 |
| 13670 9 | 21008 7 | 28301 19 | 31344 10 | 31617 14 |
| 13671 9 | 21009 7 | 28308 19 | 31345 10 | 31618 14 |
| 13672 9 | 21010 7 | 28309 19 | 31390 11 | 31619 14 |
| 13673 9 | 21011 7 | 28312 19 | 31391 11 | 31620 14 |
| 13690 9 | 21012 7 | 28315 19 | 31394 11 | 31621 14 |
| 13691 9 | 21013 7 | 28317 19 | 31395 11 | 31622 14 |
| 13693 9 | 21014 7 | 28319 19 | 31425 12 | 31623 14 |
| 13694 9 | 21015 7 | 28327 20 | 31428 12 | 31624 14 |
| 15000 8 | 21017 7 | 28329 20 | 31429 12 | 31626 14 |
| 15003 8 | 21019 7 | 28339 20 | 31430 12 | 31627 14 |
| 15050 8 | 21020 7 | 28340 20 | 31431 12 | 31628 14 |
| 19767 15 | 21022 7 | 28341 20 | 31432 12 | 31630 14 |
| 20006 5 | 21024 7 | 28342 20 | 31433 12 | 31632 14 |
| 20007 5 | 21027 7 | 28346 20 | 31434 12 | 31691 14 |
| 20008 5 | 21030 7 | 28347 20 | 31435 12 | 31703 14 |
| 20009 5 | 21032 7 | 28350 18 | 31436 12 | 31704 14 |
| 20010 5 | 21040 7 | 28390 20 | 31437 12 | 31705 14 |
| 20011 5 | 21042 7 | 28391 20 | 31438 12 | 31707 14 |
| | | | | |

Item No.	Page	ı	tem No.	Page						
31708	14	32146	21	32541	26	32917	38		76212	8
31709	14	32189	22	32546	26	32923	38		76215	8
31710	14	32190	24	32551	26	32926	38		76290	8
31712	14	32196	22	32556	26	32927	39		91230	37
31713	14	32197	22	32561	26	32929	38		91256	36
31714	14	32198	22	32590	26	32930	39			
31715	14	32206	25	32592	26	32933	38			
31716	14	32209	25	32800	29	32945	39			
31718	14	32212	25	32804	36	32947	39			
31720	14	32215	25	32806	36	32973	41			
31722	14	32218	25	32807	36	32981	40			
31790	14	32221	25	32808	36	32983	40			
31805	10	32224	25	32810	36	32984	40			
31807	10	32227	25	32814	34	32985	40			
31809	10	32230	25	32816	34	32986	41			
31811	10	32233	25	32818	34	32987	41			
31813	10	32236	25	32820	34	32988	41			
31815	10	32238	25	32821	34	32989	40			
31817	10	32239	25	32826	35	32999	40			
31890	10	32240	25	32828	35	33441	17			
32005	23	32241	25	32830	35	33443	17			
32010	23	32255	25	32832	35	33445	17			
32012	23	32258	25	32834	35	33447	17			
32015	23	32261	25	32835	35	33449	17			
32017	23	32264	25	32836	35	33478	17			
32023	23	32267	25	32838	35	33481	17			
32024	23	32268	25	32841	35	33482	17			
32025	23	32270	25	32850	37	33483	17			
32026	23	32273	25	32852	37	33485	17			
32027	23	32276	25	32854	37	33486	17			
32028	23	32278	25	32859	37	33487	17			
32031	23	32280	25	32860	37	33490	17			
32034	23	32288	26	32861	35	35811	24			
32039	23	32291	25	32867	33	35812	24			
32042	23	32292	25	32868	33	35844	21			
32045	23	32293	25	32869	33	35845	21			
32046	21	32294	25	32870	36	35890				
32049	21	32296	25	32871	28	35891	24			
32052	21	32302	24	32872	28	38006	18			
32055	21	32303	24	32873	28	38007	18			
32058	21	32304	24	32874	31	38016	27			
32090	23	32305	24	32875	28	38017	27			
32091	23	32306	24	32876	30	38018	27			
32092	23	32308	24	32877	30	38025	18			
32093	24	32366	24	32878	31	40800	15			
32094	24	32390	41	32879	31	75205	16			
32095	24	32505	26	32888	32	75210	16			
32100	23	32511	26	32889	33	75215	16			
32101	23	32516	26	32891	32	75220	16			
32102	23	32521	26	32892	32	75302	16			
32103	23	32526	26	32894	32	75304	16			
32104	23	32531	26	32895	32	76208	8			
32145	21	32536	26	32896	31	76210	8			





Insulation Test



Puncture Test



Cold Impact Test



Flame Resistance Test



Material Integrity Test



Adhesion Test

Subject to change without notice ©2013 Willi Hahn Corporation

®Torx is a registered trademark of Acument Intellectual Properties LLC.



Presented By:



CARBIDE

(800) 346-8274 fax: 253-476-1321

email: sales@carbideprocessors.com www.carbideprocessors.com

Catalog Item No. 99919 version - 3/1/13



99060.wo - Product Guide



99004.wo - Shop Tools Catalog



99006.wo - Tech Tools Catalog



99002.wo - Screwdrivers Catalog



99951.wo - Bits Catalog



99001.wo - TorqueControl Catalog



99934.wo - Hex Tools Catalog



99914.wo - TORX Catalog



Priescional Priesc